

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Raffinate 1

REACH Registration Number : 01-2119474204-43-0013, 01-2119474204-43-XXXX

Substance name : hydrocarbons, C4, steam-cracker distillate

EC-No. : 295-405-4

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Raw material in chemical industry, Manufacture, Use as an intermediate

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer : Borealis Polymers Oy  
P.O.Box 330, FI-06101 Porvoo, Finland  
Telephone: +358 9 394900

Supplier : Borealis AG  
Trabrennstrasse 6-8, 1020 Vienna, Austria  
Telephone: +43 1 22400 0

E-mail address : [sds@borealisgroup.com](mailto:sds@borealisgroup.com)

#### 1.4 Emergency telephone number

||+1 760 476 3962 (3E), Access code: 336296

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1A	H220: Extremely flammable gas.
Gases under pressure, Liquefied gas	H280: Contains gas under pressure; may explode if heated.
Germ cell mutagenicity, Category 1B	H340: May cause genetic defects.
Carcinogenicity, Category 1A	H350: May cause cancer.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.  
H340 May cause genetic defects.  
H350 May cause cancer.

Precautionary statements

:

#### Prevention:

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 In case of leakage, eliminate all ignition sources.

#### Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

#### Additional Labelling

Restricted to professional users.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Substance name : hydrocarbons, C4, steam-cracker distillate

EC-No. : 295-405-4

#### Components

Chemical name	CAS-No. EC-No.	Concentration (%) w/w)	M-Factor, SCL, ATE
Substance of unknown or variable composition, complex reaction products or biological material (UVCB) :			
Hydrocarbons, C4, steam-cracker distillate; Petroleum gas	92045-23-3 295-405-4	<= 100	
Main constituents :			
butene	25167-67-3 246-689-3	>= 30 - < 50	
2-methylpropene	115-11-7 204-066-3	>= 30 - < 50	
butane	106-97-8 203-448-7	>= 30 - < 50	
butene, mixed-1-and-2-isomers	107-01-7 203-452-9	>= 10 - < 20	
1,3-butadiene	106-99-0 203-450-8	>= 0,1 - < 1	

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Where there is potential for exposure:  
Restrict access to authorised persons.  
Provide specific activity training to operators to minimise exposures.  
Wear suitable gloves and coveralls to prevent skin contamination.  
Avoid and prevent all contact and exposure.  
Move the victim to fresh air.  
In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

- |                         |  |
|-------------------------|--|
| If inhaled              | : Move to fresh air.<br>Do not leave the victim unattended.<br>Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.<br>Keep patient warm and at rest.<br>Seek medical advice immediately.<br>If breathing is irregular or stopped, administer artificial respiration.<br>If unconscious place in recovery position. |
| In case of skin contact | : Wash frost-bitten areas with plenty of water. Do not remove clothing.<br>Seek medical advice.  |
| In case of eye contact  | : Remove contact lenses.<br>Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.<br>Keep eye wide open while rinsing.  |
| If swallowed            | : Not probable:<br>The product evaporates readily.   |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |
|----------|---|
| Symptoms | : Shortness of breath<br>Unconsciousness<br>Frostbite   |
| Risks    | : May cause effects on the central nervous system, resulting in lowering of consciousness.<br>May cause genetic defects.<br>May cause cancer. |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |
|-----------|---|
| Treatment | : Artificial respiration and/or oxygen may be necessary.<br>There is no specific antidote available.<br>Treat frost-bitten areas as needed. |
|-----------|---|

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Dry powder<br>Carbon dioxide (CO <sub>2</sub> )<br>Foam<br>Water mist |
| Unsuitable extinguishing media | : High volume water jet   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Vapours are heavier than air and may spread along floors.  
Flash back possible over considerable distance.  
Cool closed containers exposed to fire with water spray.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Hazardous decomposition products formed under fire conditions.  
See chapter 10.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

Further information : Attempt to stop leakage without personal risk.  
If conditions permit, let fire burn itself out.  
Cool tanks with water spray.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal protection through wearing a tightly closed chemical protection suit and a self-contained breathing apparatus.  
Do not breathe vapours.  
Ensure adequate ventilation, especially in confined areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded.  
Avoid all contact with the product.  
Keep people away from and upwind of spill/leak.  
Attempt to stop leakage without personal risk.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so.  
Prevent product from entering environment and drains.  
If major spillage occurs, contact the proper local authorities.

### 6.3 Methods and material for containment and cleaning up

Attempt to stop leakage without personal risk.  
Ventilate the area.  
Allow to evaporate.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 6.4 Reference to other sections

For personal protection see section 8.

For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : To be handled by trained personnel only.  
Consider technical advances and process upgrades (including automation) for the elimination of releases.  
Minimise exposure using measures such as closed systems, dedicated facilities and suitable general / local exhaust ventilation.  
Drain down and flush system prior to equipment opening or maintenance.  
Clean / flush equipment, where possible, prior to maintenance.  
Consider the need for risk based health surveillance.  
Ensure safe systems of work or equivalent arrangements are in place to manage risks.  
Regularly inspect, test and maintain all control measures.  
Wear respiratory protection when its use is identified for certain contributing scenarios.  
Prevent leaks by checking valves, pipelines and joints regularly.  
Handle and open container with care.  
Dispose of rinse water in accordance with local and national regulations.  
Vapours are heavier than air and may spread along floors.
- Advice on protection against fire and explosion : Vapours may form explosive mixtures with air. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Ensure adequate ventilation.  
Keep product and empty container away from heat and sources of ignition.
- Hygiene measures : Ensure adequate ventilation, especially in confined areas.  
Smoking, eating and drinking should be prohibited in the application area.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep only in the original container in a cool, well-ventilated place. Keep product and empty container away from heat and sources of ignition. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Bund storage facilities to prevent soil and water pollution in the event of spillage. Store in accordance with the particular

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

national regulations.

Further information on storage conditions : Keep locked up or in an area accessible only to qualified or authorised persons. Ensure adequate ventilation.

Advice on common storage : Keep away from incompatible materials.  
See chapter 10.

### 7.3 Specific end use(s)

Specific use(s) : Not applicable

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1,3-butadiene	106-99-0	TWA	1 ppm 2,2 mg/m <sup>3</sup>	2004/37/EC
Further information	Carcinogens or mutagens			

Substances for which there are Community workplace exposure limits.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Raffinate 1	Consumers	Inhalation	Long-term systemic effects	0,265 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	2,21 mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Raffinate 1		
Remarks:	No data available	

### 8.2 Exposure controls

#### Engineering measures

Minimise exposure using measures such as closed systems, dedicated facilities and suitable general / local exhaust ventilation.

Ensure safe systems of work or equivalent arrangements are in place to manage risks.

Regularly inspect, test and maintain all control measures.

#### Personal protective equipment

Eye protection : Safety goggles or face-shield.

Hand protection

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

- Material : Cold-insulating gloves (e.g. nitrile rubber).
- Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. This recommendation is only valid for the product mentioned in the safety data sheet and provided by us and for the application specified by us.
- Skin and body protection : Wear suitable protective clothing and rubber boots.
- Respiratory protection : In case of insufficient ventilation: Self-contained breathing apparatus.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

### Environmental exposure controls

- General advice : Prevent further leakage or spillage if safe to do so. Prevent product from entering environment and drains. If major spillage occurs, contact the proper local authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : Liquefied gas
- Colour : colourless
- Odour : characteristic
- Melting range : -185 - -106 °C
- Boiling point : -11,73 - 10,9 °C
- Upper explosion limit / Upper flammability limit : 12 %(V)
- Lower explosion limit / Lower flammability limit : 1,6 %(V)
- Flash point : < -18 °C
- pH : Not applicable (gaseous)
- Viscosity
- Viscosity, kinematic : Not applicable (gaseous)
- Solubility(ies)
- Water solubility : 135,6 - 792,3 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Partition coefficient: n-octanol/water	:	log Pow: 1,40 - 2,89
Vapour pressure	:	Not applicable
Density	:	630 g/cm <sup>3</sup>
Relative vapour density	:	1,9
Particle size	:	Not applicable

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Not applicable
Self-ignition	:	324 - 465 °C
Surface tension	:	Not applicable
Molecular weight	:	Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.  
Risk of violent reaction.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixtures with air.

### 10.4 Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.

### 10.5 Incompatible materials

Materials to avoid : Air  
Ozone  
Oxidizing agents  
Chlorine  
Hydrogen chloride

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Hydrogen fluoride  
chlorine dioxide  
Nitrogen oxides (NOx)  
Copper  
Copper alloys  
phenol  
crotonaldehyde  
hydroquinone

### 10.6 Hazardous decomposition products

Under fire conditions:

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Product:

Acute oral toxicity : Remarks: study technically not feasible  
(gaseous)

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,3 mg/l  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403  
Remarks: Read-across (Analogy)

Acute dermal toxicity : Remarks: study technically not feasible  
(gaseous)

Acute toxicity (other routes of administration) : Remarks: No data available

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Product:

Result : No skin irritation  
Remarks : Read-across (Analogy)

#### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### **Product:**

Result : No eye irritation  
Remarks : Read-across (Analogy)

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Based on available data, the classification criteria are not met.

#### **Respiratory sensitisation**

Based on available data, the classification criteria are not met.

### **Product:**

Remarks : study technically not feasible

### **Germ cell mutagenicity**

May cause genetic defects.

### **Product:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: positive  
Test substance: 1,3-butadiene

Genotoxicity in vivo : Test Type: Cytogenetic assay  
Species: Mouse  
Application Route: Inhalation  
Method: OECD Test Guideline 478  
Result: positive

### **Carcinogenicity**

May cause cancer.

### **Product:**

Application Route : Inhalation  
LOAEL : 2,21 mg/l  
Remarks : Positive evidence from human epidemiological studies  
(inhalation)

### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

### **Product:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Application Route: Inhalation  
General Toxicity - Parent: No observed adverse effect  
concentration: 7.131 mg/m<sup>3</sup>  
Method: OECD Test Guideline 422

Effects on foetal development : Test Type: Fertility/early embryonic development  
Developmental Toxicity: NOAEC Parent: 88 mg/m<sup>3</sup>

### STOT - single exposure

Based on available data, the classification criteria are not met.

### STOT - repeated exposure

Based on available data, the classification criteria are not met.

### Repeated dose toxicity

#### Product:

Species : Rat  
NOAEL : mg/m<sup>3</sup>, 2212  
Application Route : inhalation (vapour)  
Method : OECD Test Guideline 453

### Aspiration toxicity

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Rapid evaporation of the liquid may cause frostbite.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
May cause effects on the central nervous system, resulting in lowering of consciousness.  
Absorbs into the body by inhalation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

Toxicity to fish	: LC50 : 25,37 mg/l Exposure time: 96 h Method: QSAR
Toxicity to daphnia and other aquatic invertebrates	: LC50 : 14,818 mg/l Exposure time: 48 h Method: QSAR
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 12,405 mg/l Method: QSAR
Toxicity to fish (Chronic toxicity)	: Chronic Toxicity Value: 2,564 mg/l Method: QSAR
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: Chronic Toxicity Value: 1,563 mg/l Method: QSAR

#### 12.2 Persistence and degradability

**Product:**

Biodegradability	: Remarks: Not readily biodegradable.
------------------	---------------------------------------

#### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation	: Remarks: Bioaccumulation not expected: Partition coefficient (n-octanol/water) log Pow < 3.
-----------------	---

#### 12.4 Mobility in soil

**Product:**

Mobility	: Remarks: The product evaporates readily.
----------	--

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..
------------	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of as hazardous waste in compliance with local and national regulations.  
European waste code:  
07 01 99 (wastes not otherwise specified (basic organic chemicals))  
Where possible recycling is preferred to disposal or incineration.

Contaminated packaging : Dispose of as hazardous waste in compliance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1012  
IMDG : UN 1012

### 14.2 UN proper shipping name

ADR : BUTYLENES MIXTURE  
IMDG : BUTYLENE

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 14.3 Transport hazard class(es)

ADR : 2  
IMDG : 2.1

### 14.4 Packing group

ADR  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1  
Tunnel restriction code : (B/D)

IMDG  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### 14.5 Environmental hazards

ADR  
Environmentally hazardous : no

IMDG  
Marine pollutant : no

### 14.6 Special precautions for user

Remarks : SDS: No specific instructions needed.  
The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Category		Quantity 1	Quantity 2
P2	FLAMMABLE GASES	10 t	50 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Other regulations:

Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.

### Full text of other abbreviations

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work  
2004/37/EC / TWA : Long term exposure limit

### Further information

Other information : Changes since the last version are highlighted in the margin. This version replaces all previous versions.  
Issuer : Borealis, Group Product Stewardship  
Sources of key data used to compile the Safety Data Sheet : Chemical Safety Report, Hydrocarbons, C4, steam-cracker distillate, Lower Olefins and Aromatics REACH Consortium, 2021  
ECHA - Information on Registered Substances (<http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>)  
International Chemical Safety Card, 1,3-Butadiene, April 2000 (<http://www.inchem.org/documents/icsc/icsc/eics0017.htm>)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

**Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.**

**It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.**

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
ES1	Use at industrial sites, Manufacture of substance
ES2	Use at industrial sites, Use as an intermediate

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### ES1: Manufacture of substance

#### 1.1. Title section

**Structured Short Title** : Use at industrial sites, Manufacture of substance

Environment		
<b>CS1</b>	<b>Manufacture of substance</b>	ERC1
Worker		
<b>CS2</b>	<b>General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General measures applicable to all activities</b>	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28
<b>CS3</b>	<b>General exposures (closed systems), Indoor</b>	PROC1
<b>CS4</b>	<b>General exposures (closed systems), Outdoor</b>	PROC1
<b>CS5</b>	<b>General exposures (closed systems), Local exhaust ventilation, Indoor</b>	PROC2
<b>CS6</b>	<b>General exposures (closed systems), Local exhaust ventilation, Indoor</b>	PROC3
<b>CS7</b>	<b>General exposures (open systems), Local exhaust ventilation, Indoor</b>	PROC4
<b>CS8</b>	<b>General exposures (open systems), Respiratory protection, Indoor</b>	PROC4
<b>CS9</b>	<b>General exposures (open systems), Respiratory protection, Outdoor</b>	PROC4
<b>CS10</b>	<b>Process sampling, Local exhaust ventilation, Indoor</b>	PROC9
<b>CS11</b>	<b>Process sampling, Respiratory protection, Indoor</b>	PROC9
<b>CS12</b>	<b>Process sampling, Respiratory protection, Outdoor</b>	PROC9
<b>CS13</b>	<b>Laboratory activities, Local exhaust ventilation, Indoor</b>	PROC15
<b>CS14</b>	<b>Bulk transfers, Closed systems, Local exhaust ventilation, Indoor</b>	PROC8b
<b>CS15</b>	<b>Bulk transfers, Open systems, Local exhaust ventilation, Indoor</b>	PROC8b
<b>CS16</b>	<b>Bulk transfers, Open systems, Respiratory protection, Outdoor</b>	PROC8b
<b>CS17</b>	<b>Equipment cleaning and maintenance, Local exhaust ventilation, Indoor</b>	PROC8a, PROC28

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

<b>CS18</b>	<b>Storage, Outdoor</b>	PROC1, PROC2
<b>CS19</b>	<b>Storage, Indoor</b>	PROC1, PROC2

## 1.2. Conditions of use affecting exposure

### 1.2.1. Control of environmental exposure: Manufacture of the substance (ERC1)

Amount used, frequency and duration of use (or from service life)	
Annual amount per site	: 261000 tonnes/year
Daily amount per site	: 870 tonnes/day
Technical and organisational conditions and measures	
Vapour recovery (e.g. adsorption) or other technique for reducing volatiles emissions (incineration, thermal oxidation) Air - minimum efficiency of 90 %	
Acclimated biological treatment Water - minimum efficiency of 70 %	
No release to wastewater from process as such, wastewater emissions limited to release generated from final equipment cleaning step using water	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 40

**1.2.2. Control of worker exposure: General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General measures applicable to all activities**  
**Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) /**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

**Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Use as laboratory reagent (PROC15) / Manual maintenance (cleaning and repair) of machinery (PROC28)**

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquefied gas
Amount used, frequency and duration of use (or from service life)	
Duration	: Covers daily exposures up to 8 hours (unless stated differently).
Conditions and measures related to personal protection, hygiene and health evaluation	
General measures (eye irritants) Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance. Handle in accordance with good industrial hygiene and safety practice.	

**1.2.3. Control of worker exposure: General exposures (closed systems), Indoor  
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)**

### Technical and organisational conditions and measures

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Occupational Health and Safety Management System: Advanced  
Use in closed process

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.  
Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.4. Control of worker exposure: General exposures (closed systems), Outdoor Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

### Technical and organisational conditions and measures

Use in closed process

Occupational Health and Safety Management System: Advanced

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.  
Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.5. Control of worker exposure: General exposures (closed systems), Local exhaust ventilation, Indoor Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 4 h/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Use in closed, continuous process with occasional controlled exposure

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Handle substance within a predominantly closed system provided with extract ventilation.  
Inhalation - minimum efficiency of 95 %

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.  
Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

Temperature : Assumes process temperature up to 20 °C

### 1.2.6. Control of worker exposure: General exposures (closed systems), Local exhaust ventilation, Indoor

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced  
Closed batch process with occasional controlled exposure

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Handle substance within a predominantly closed system provided with extract ventilation.  
Inhalation - minimum efficiency of 95 %

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.  
Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Temperature	:	Assumes process temperature up to 20 °C
-------------	---	---

### 1.2.7. Control of worker exposure: General exposures (open systems), Local exhaust ventilation, Indoor

Chemical production where opportunity for exposure arises (PROC4)

Amount used, frequency and duration of use (or from service life)		
Use frequency	:	Covers use up to 1 h/day
Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).		
Local exhaust ventilation Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 95 %		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %		
Other conditions affecting workers exposure		
Indoor or outdoor use	:	Indoor use
Temperature	:	Assumes process temperature up to 20 °C

### 1.2.8. Control of worker exposure: General exposures (open systems), Respiratory protection, Indoor

Chemical production where opportunity for exposure arises (PROC4)

Amount used, frequency and duration of use (or from service life)		
Use frequency	:	Covers use up to 1 h/day
Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374.		



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 10

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.9. Control of worker exposure: General exposures (open systems), Respiratory protection, Outdoor Chemical production where opportunity for exposure arises (PROC4)

#### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

#### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 20

### Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.10. Control of worker exposure: Process sampling, Local exhaust ventilation, Indoor Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

#### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 0,25 h/day

#### Technical and organisational conditions and measures

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Occupational Health and Safety Management System: Advanced

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Ensure samples are obtained under containment or extract ventilation.

or

Sample via a closed loop or other system to avoid exposure.

Inhalation - minimum efficiency of 95 %

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.11. Control of worker exposure: Process sampling, Respiratory protection, Indoor Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

#### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 0,25 h/day

#### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 10

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.12. Control of worker exposure: Process sampling, Respiratory protection, Outdoor

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)	
Use frequency	: Covers use up to 0,25 h/day
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Wear suitable respiratory protection. Efficiency: APF 20	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Outdoor use
Temperature	: Assumes process temperature up to 20 °C

### 1.2.13. Control of worker exposure: Laboratory activities, Local exhaust ventilation, Indoor Use as laboratory reagent (PROC15)

Amount used, frequency and duration of use (or from service life)	
Use frequency	: Covers use up to 4 h/day
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Handle in a fume cupboard or under extract ventilation. Inhalation - minimum efficiency of 90 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.14. Control of worker exposure: Bulk transfers, Closed systems, Local exhaust ventilation, Indoor

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Ensure material transfers are under containment or extract ventilation.

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.15. Control of worker exposure: Bulk transfers, Open systems, Local exhaust ventilation, Indoor

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Ensure material transfers are under containment or extract ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.16. Control of worker exposure: Bulk transfers, Open systems, Respiratory protection, Outdoor Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

#### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 0,25 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 20

### Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

### 1.2.17. Control of worker exposure: Equipment cleaning and maintenance, Local exhaust ventilation, Indoor Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

#### Amount used, frequency and duration of use (or from service life)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Use frequency	: Covers use up to 4 h/day
<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Drain down and flush system prior to equipment break-in or maintenance. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Respiratory protection Efficiency: APF 10	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 1.2.18. Control of worker exposure: Storage, Outdoor

**Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Store substance within a closed system.	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Outdoor use
Temperature	: Assumes process temperature up to 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 1.2.19. Control of worker exposure: Storage, Indoor

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)	
Use frequency	: Covers use up to 1 h/day
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Store substance within a closed system.	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: Manufacture of the substance (ERC1)

Release route	Release rate	Release estimation method
Water	783 kg/day	
Air	217,5 kg/day	

Compartment	Exposure level	RCR
Man via environment - Inhalation	0,169 mg/m <sup>3</sup> (EUSES v2.1)	0,638

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 1.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

### 1.3.4. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

### 1.3.5. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 1.3.6. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,145	1,3-butadiene

### 1.3.7. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 1.3.8. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 1.3.9. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,145	1,3-butadiene

### 1.3.10. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 1.3.11. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 1.3.12. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,145	1,3-butadiene

### 1.3.13. Worker exposure: Use as laboratory reagent (PROC15)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,413 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,187	1,3-butadiene

### 1.3.14. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 1.3.15. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 1.3.16. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,241 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,109	1,3-butadiene

### 1.3.17. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 1.3.18. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

**refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

**1.3.19. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,161 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,073	1,3-butadiene

### 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### ES2: Use as an intermediate

#### 2.1. Title section

<b>Structured Short Title</b>	: Use at industrial sites, Use as an intermediate
-------------------------------	---

Environment		
<b>CS1</b>	<b>Use as an intermediate</b>	ERC6a
Worker		
<b>CS2</b>	<b>General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General measures applicable to all activities</b>	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28
<b>CS3</b>	<b>General exposures (closed systems), Indoor</b>	PROC1
<b>CS4</b>	<b>General exposures (closed systems), Outdoor</b>	PROC1
<b>CS5</b>	<b>General exposures (closed systems), Local exhaust ventilation, Indoor</b>	PROC2
<b>CS6</b>	<b>General exposures (closed systems), Local exhaust ventilation, Indoor</b>	PROC3
<b>CS7</b>	<b>General exposures (open systems), Local exhaust ventilation, Indoor</b>	PROC4
<b>CS8</b>	<b>General exposures (open systems), Respiratory protection, Indoor</b>	PROC4
<b>CS9</b>	<b>General exposures (open systems), Respiratory protection, Outdoor</b>	PROC4
<b>CS10</b>	<b>Process sampling, Local exhaust ventilation, Indoor</b>	PROC9
<b>CS11</b>	<b>Process sampling, Respiratory protection, Indoor</b>	PROC9
<b>CS12</b>	<b>Process sampling, Respiratory protection, Outdoor</b>	PROC9
<b>CS13</b>	<b>Laboratory activities, Local exhaust ventilation, Indoor</b>	PROC15
<b>CS14</b>	<b>Bulk transfers, Closed systems, Local exhaust ventilation, Indoor</b>	PROC8b
<b>CS15</b>	<b>Bulk transfers, Open systems, Local exhaust ventilation, Indoor</b>	PROC8b
<b>CS16</b>	<b>Bulk transfers, Open systems, Respiratory protection, Indoor</b>	PROC8b
<b>CS17</b>	<b>Equipment cleaning and maintenance, Local exhaust ventilation, Indoor</b>	PROC8a, PROC28

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

<b>CS18</b>	<b>Storage, Outdoor</b>	PROC1, PROC2
<b>CS19</b>	<b>Storage, Indoor</b>	PROC1, PROC2

## 2.2. Conditions of use affecting exposure

### 2.2.1. Control of environmental exposure: Use of intermediate (ERC6a)

Amount used, frequency and duration of use (or from service life)	
Annual amount per site	: 60000 tonnes/year
Daily amount per site	: 200 tonnes/day
Technical and organisational conditions and measures	
Typical measures to maintain workplace concentrations of airborne VOCs and particulates below respective OELs: e.g. thermal wet scrubber – gas removal and/or air filtration – particle removal and/or thermal oxidation and/or vapour recovery – adsorption. Upgrade of the system in place or additional air treatment measures, such as wet scrubber and/or air filtration and/or thermal oxidation and/or vapour recovery systems, in order to achieve a reduction of the air emissions. Air - minimum efficiency of 50 %	
Process optimized for highly efficient use of raw materials (very minimal environmental release)	
Acclimated biological treatment Water - minimum efficiency of 70 %	
No release to wastewater from process as such, wastewater emissions limited to release generated from final equipment cleaning step using water	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 40

### 2.2.2. Control of worker exposure: General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General measures applicable to all activities

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Use as laboratory reagent (PROC15) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquefied gas
Amount used, frequency and duration of use (or from service life)	
Duration	: Covers daily exposures up to 8 hours (unless stated differently).
Conditions and measures related to personal protection, hygiene and health evaluation	
General measures (eye irritants) Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance. Handle in accordance with good industrial hygiene and safety practice.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 2.2.3. Control of worker exposure: General exposures (closed systems), Indoor Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced Use in closed process	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 2.2.4. Control of worker exposure: General exposures (closed systems), Outdoor Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures	
Use in closed process	
Occupational Health and Safety Management System: Advanced	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Outdoor use
Temperature	: Assumes process temperature up to 40 °C

### 2.2.5. Control of worker exposure: General exposures (closed systems), Local exhaust ventilation, Indoor

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

**Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Handle substance within a predominantly closed system provided with extract ventilation. Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes process temperature up to 20 °C

**2.2.6. Control of worker exposure: General exposures (closed systems), Local exhaust ventilation, Indoor**

**Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)**

Amount used, frequency and duration of use (or from service life)	
Use frequency	: Covers use up to 4 h/day
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced Closed batch process with occasional controlled exposure	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Handle substance within a predominantly closed system provided with extract ventilation. Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

Temperature : Assumes process temperature up to 20 °C

### 2.2.7. Control of worker exposure: General exposures (open systems), Local exhaust ventilation, Indoor

Chemical production where opportunity for exposure arises (PROC4)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Local exhaust ventilation

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of 95 %

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 2.2.8. Control of worker exposure: General exposures (open systems), Respiratory protection, Indoor

Chemical production where opportunity for exposure arises (PROC4)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 10

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

## 2.2.9. Control of worker exposure: General exposures (open systems), Respiratory protection, Outdoor

Chemical production where opportunity for exposure arises (PROC4)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 80 %

Wear suitable respiratory protection.

Efficiency: APF 20

### Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

## 2.2.10. Control of worker exposure: Process sampling, Local exhaust ventilation, Indoor Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

### Amount used, frequency and duration of use (or from service life)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Use frequency	: Covers use up to 0,25 h/day
<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Local exhaust ventilation Ensure samples are obtained under containment or extract ventilation. or Sample via a closed loop or other system to avoid exposure. Inhalation - minimum efficiency of 95 %	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 2.2.11. Control of worker exposure: Process sampling, Respiratory protection, Indoor Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

<b>Amount used, frequency and duration of use (or from service life)</b>	
Use frequency	: Covers use up to 0,25 h/day
<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 % Wear suitable respiratory protection. Efficiency: APF 10	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Temperature	:	Assumes process temperature up to 20 °C
-------------	---	---

### 2.2.12. Control of worker exposure: Process sampling, Respiratory protection, Outdoor Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)		
Use frequency	:	Covers use up to 0,25 h/day
Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Provide a basic standard of general ventilation (1 to 3 air changes per hour).		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374.		
Dermal - minimum efficiency of 80 %		
Wear suitable respiratory protection.		
Efficiency: APF 20		
Other conditions affecting workers exposure		
Indoor or outdoor use	:	Outdoor use
Temperature	:	Assumes process temperature up to 20 °C

### 2.2.13. Control of worker exposure: Laboratory activities, Local exhaust ventilation, Indoor Use as laboratory reagent (PROC15)

Amount used, frequency and duration of use (or from service life)		
Use frequency	:	Covers use up to 4 h/day
Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).		
Local exhaust ventilation		
Inhalation - minimum efficiency of 95 %		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374.		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Dermal - minimum efficiency of 80 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 2.2.14. Control of worker exposure: Bulk transfers, Closed systems, Local exhaust ventilation, Indoor

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

Ensure material transfers are under containment or extract ventilation.

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

### 2.2.15. Control of worker exposure: Bulk transfers, Open systems, Local exhaust ventilation, Indoor

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Local exhaust ventilation  
Ensure material transfers are under containment or extract ventilation.  
Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.  
Dermal - minimum efficiency of 95 %

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

## 2.2.16. Control of worker exposure: Bulk transfers, Open systems, Respiratory protection, Indoor Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### Amount used, frequency and duration of use (or from service life)

Use frequency : Covers use up to 1 h/day

### Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.  
Dermal - minimum efficiency of 95 %

Wear suitable respiratory protection.  
Efficiency: APF 10

### Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

## 2.2.17. Control of worker exposure: Equipment cleaning and maintenance, Local exhaust ventilation, Indoor Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

<b>Amount used, frequency and duration of use (or from service life)</b>	
Use frequency	: Covers use up to 0,25 h/day
<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Drain down and flush system prior to equipment break-in or maintenance. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 2.2.18. Control of worker exposure: Storage, Outdoor

**Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

<b>Technical and organisational conditions and measures</b>	
Occupational Health and Safety Management System: Advanced	
Store substance within a closed system.	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Outdoor use
Temperature	: Assumes process temperature up to 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 2.2.19. Control of worker exposure: Storage, Indoor

**Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Amount used, frequency and duration of use (or from service life)	
Use frequency	: Covers use up to 1 h/day
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Use in closed, continuous process with occasional controlled exposure Store substance within a closed system.	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 80 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure: Use of intermediate (ERC6a)

Release route	Release rate	Release estimation method
Water	60 kg/day	
Air	250 kg/day	

Compartment	Exposure level	RCR
Man via environment - Inhalation	0,059 mg/m <sup>3</sup> (EUSES v2.1)	0,221



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 2.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

### 2.3.4. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

### 2.3.5. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,344 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,156	1,3-butadiene

### 2.3.6. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,413 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,187	1,3-butadiene

### 2.3.7. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

### 2.3.8. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 2.3.9. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,145	1,3-butadiene

### 2.3.10. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 2.3.11. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,276 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,125	1,3-butadiene

### 2.3.12. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,145	1,3-butadiene

### 2.3.13. Worker exposure: Use as laboratory reagent (PROC15)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,413 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,187	1,3-butadiene

### 2.3.14. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 2.3.15. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,207 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,093	1,3-butadiene

### 2.3.16. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,413 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,187	1,3-butadiene

### 2.3.17. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,344 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,156	1,3-butadiene

### 2.3.18. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Raffinate 1

Version 6.0

Revision Date: 14.03.2024

Former date: 11.11.2022

**refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,00321 mg/m <sup>3</sup> (ECETOC TRA worker v3)	< 0,01	1,3-butadiene

**2.3.19. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,069 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0,031	1,3-butadiene

## 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).