# Polypropylene ED022HPB

Polypropylene Compound

### Description

ED022HPB is a polypropylene copolymer intended for injection moulding.

### **Applications**

ED022HPB has been developed especially for applications like:

Structural parts

### **Special Features**

Good stiffness and impact balance Low density

#### **Physical Properties**

Values determined on standard injection moulded specimens conditioned at 23°C and 50% relative humidity after at least 96 hours storage time.

Spare-wheel carrier

Good flowability

Property	Typical Value Test Method Data should not be used for specification work		
Density (23 °C)	920 kg/m³	ISO 1183	
Melt Flow Rate (230 °C/2,16 kg)	6 g/10min	ISO 1133	
Flexural Modulus (2 mm/min)	1.700 MPa	ISO 178	
Tensile Stress at Yield (50 mm/min) (23 °C)	35 MPa	ISO 527-2	
Charpy Impact Strength, notched (23 °C)	3,5 kJ/m²	ISO 179/1eA	
Charpy Impact Strength, unnotched (23 °C)	35 kJ/m <sup>2</sup>	ISO 179/1eU	

### **Processing Techniques**

The actual conditions will depend on the type of equipment used.

ED022HPB is easy to process with standard injection moulding machines. To avoid residual humidity from transport or storage, the material should be pre-dried approximately 2h at 95° - 105°C. Following moulding parameters should be used as guidelines:

Melt temperature Holding pressure

Mould temperature Injection speed 180 - 210 °C 50-70% of injection pressure 20 - 40 °C Low to medium

#### Storage

**ED022HPB** ED022HPB should be stored in dry conditions at temperatures below 50 °C and protected from UV-light. Improper storage can initiate degradation, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.

#### Safety

Please see our "Safety data sheet" / "Product safety information sheet" for details on various aspects of safety, recovery and disposal of the product. For more information, contact your Borealis representative.

#### Recycling

The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.

Borealis Brasil S/A | Av. Osvaldo Berto, 700 | Bairro do Pinhal | Distrito Industrial Alfredo Rela | CEP: 13255-840 | Itatiba - SP | Brasil | Website <u>www.borealisgroup.com</u>



## Polypropylene ED022HPB

#### **Regional Availability**

South America For information on regional availability please contact Borealis Sales Representative.

#### Disclaimer

## The product(s) mentioned herein are not intended to be used for medical, pharmaceutical or healthcare applications and we do not support their use for such applications.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of any Borealis product in conjunction with any other products and/or materials. The information contained herein relates exclusively to our products when not used in conjunction with any other material unless as specifically provided for in the test methods stated above.

Borealis Brasil S/A | Av. Osvaldo Berto, 700 | Bairro do Pinhal | Distrito Industrial Alfredo Rela | CEP: 13255-840 | Itatiba - SP | Brasil | Website <u>www.borealisgroup.com</u>

