

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

SECTION 1. IDENTIFICATION

Product name : EG2402SYU

Manufacturer or supplier's details

Supplier : Borealis Compounds Inc
176 Thomas Road, NJ 07865 Port Murray, United States of America (USA)
Telephone: +1 908 850 6200

E-mail address : sds@borealisgroup.com

Emergency telephone : +1 866 519 4752 (3E) Access code: 336296 Borealis Compounds Inc, Borealis North America HSE: 908-850-6200 for Monday – Friday 8-4:30pm excluding holidays

Recommended use of the chemical and restrictions on use

Recommended use : Raw material for plastics industry
Restrictions on use : Use only according to our recommendations.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Other hazards

Warning!

May form combustible dust concentrations in air (during processing).
The product burns, but is not classified as flammable.

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.
H361f Suspected of damaging fertility.

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

The following percentage of the mixture consists of ingredient(s) with unknown acute oral toxicity: 1.602 %

The following percentage of the mixture consists of ingredient(s) with unknown acute dermal toxicity: 1.602 %

The following percentage of the mixture consists of ingredient(s) with unknown acute inhalation toxicity: 1.602 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : The product is a polypropylene polymer.
It contains post-industrial recycled polymer.
It contains talc.

Components

Chemical name	CAS-No.	Concentration (% w/w)
magnesium silicate	14807-96-6	Trade secret ($\geq 15 - \leq 40$)
calcium carbonate	471-34-1	Trade secret ($\geq 7 - \leq 13$)
magnesium carbonate	546-93-0	Trade secret ($\geq 1 - \leq 5$)
carbon black	1333-86-4	Trade secret ($\geq 0.5 - \leq 1.5$)
titaniumdioxide	13463-67-7	Trade secret ($\geq 0.5 - \leq 1.5$)
bis(2,2,6,6-tetramethyl-4-piperidiny)decanedioate	52829-07-9	Trade secret ($\geq 0.1 - \leq 1$)
N,N''-(1,2-ethanediy)bis(((4,6-bis(butyl(1,2,2,6,6-pentamethyl-4-piperidiny)amino)-1,3,5-triazin-2-	106990-43-6	Trade secret ($\geq 0.1 - \leq 1$)

Borealis GmbH | Trabrennstrasse 6-8 | 1020 Vienna | Austria
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333
FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

yl)imino)-3,1-propanediyl))bis(N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,3,5-triazine- 2,4,6-triamine		
---	--	--

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and plenty of water.
Call a physician if irritation develops or persists.
If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth with water.
Consult a physician if necessary.
- Most important symptoms and effects, both acute and delayed : Inhalation of dust may irritate the respiratory tract.
Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.
Skin contact may provoke the following symptoms:
Irritation
May cause an allergic skin reaction.
Suspected of damaging fertility.
May cause an allergic skin reaction.
Suspected of damaging fertility.
- Notes to physician : Treat symptomatically.
No specific instructions needed.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water in spread jet, dry chemicals, foam or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Principal toxicant in the smoke is carbon monoxide.

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Borealis GmbH | Trabrennstasse 6-8 | 1020 Vienna | Austria
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333
FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation.
Use personal protective equipment.
- Environmental precautions : Should not be released into the environment.
- It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment.
- Methods and materials for containment and cleaning up : Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Non-sparking tools should be used.
Vacuum or sweep up spill.
All spill of material must be removed immediately to prevent slipping accidents.
Recycle or dispose loose material properly.
Do not flush into surface water or sanitary sewer system.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Dust from the product gives a potential risk for dust explosion.
All equipment shall be grounded.
Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
- Advice on safe handling : During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released.
Provide adequate ventilation.
Local exhaust ventilation may be necessary.
Avoid inhalation of dust and decomposition fumes.
Avoid contact with skin and eyes.
- Conditions for safe storage : Safety aspects do not require any special precautions in terms of storage.
- Further information on storage stability : Keep in a dry place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
magnesium silicate	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Res-	2 mg/m ³	ACGIH

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

		pirable particulate matter)		
calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
magnesium carbonate	546-93-0	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
		TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1
		TWA	3.5 mg/m ³	OSHA P0
		TWA	0.1 mg/m ³ (PAHs)	NIOSH REL
titaniumdioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0

Engineering measures : Provide adequate ventilation.
Local exhaust ventilation may be necessary.

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment.

Personal protective equipment

Respiratory protection : In case of dust development use dust mask.
In the case of vapor formation use a respirator with an approved filter.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han-

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Hand protection : dling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Remarks : Protective gloves

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Safety glasses

Skin and body protection : Protective clothing

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pellets

Color : natural color

Odor : Odor

Odor Threshold : No data available

pH : Not applicable insoluble

: 266 - 338 °F / 130 - 170 °C

Boiling range : Decomposes on heating.

Flash point : Not applicable (solid)

Evaporation rate : Not applicable (solid)

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapor pressure : Not applicable (solid)

Relative vapor density : Not applicable (solid)

Relative density : No data available

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Density	:	1.0 - 1.1 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable insoluble
Autoignition temperature	:	> 608 °F / > 320 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
		No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	3 - 10 mm
		Method: Image analysis (surface-based)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	The product is a stable thermoplastic.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	None known.
Hazardous decomposition products	:	Under fire conditions: Carbon monoxide During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Components:

bis(2,2,6,6-tetramethyl-4-piperidiny)decanedioate:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405
GLP : no

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Components:

N,N''-(1,2-ethanediy)bis(((4,6-bis(butyl(1,2,2,6,6-pentamethyl-4-piperidiny)amino)-1,3,5-triazin-2-yl)imino)-3,1-propanediy))bis(N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,3,5-triazine-2,4,6-triamine:

Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

IARC	Group 2A: Probably carcinogenic to humans magnesium silicate	14807-96-6
	Group 2B: Possibly carcinogenic to humans carbon black	1333-86-4
	Group 2B: Possibly carcinogenic to humans titaniumdioxide	13463-67-7

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Components:

bis(2,2,6,6-tetramethyl-4-piperidiny)decanedioate:

Effects on fetal development : Species: Rabbit
Application Route: oral (gavage)
Developmental Toxicity: NOAEL: 60 mg/kg bw/day
Method: OECD Test Guideline 414

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

GLP: yes

Reproductive toxicity - Assessment : Suspected of damaging fertility.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Components:

N,N''-(1,2-ethanediybis(((4,6-bis(butyl(1,2,2,6,6-pentamethyl-4-piperidiny)amino)-1,3,5-triazin-2-yl)imino)-3,1-propanediy))bis(N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,3,5-triazine-2,4,6-triamine:

Species : Rat
NOAEL : 5 mg/kg bw/day
Method : OECD Test Guideline 408
Target Organs : lymphatic system

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : Inhalation of dust may irritate the respiratory tract.
Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bis(2,2,6,6-tetramethyl-4-piperidiny)decanedioate:

Toxicity to fish : LC50 (Lepomis macrochirus (bluegill sunfish)): 4.4 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 8.58 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): 0.705 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.23 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

N,N''-(1,2-ethanediy)lbis(((4,6-bis(butyl(1,2,2,6,6-pentamethyl-4-piperidiny)amino)-1,3,5-triazin-2-yl)imino)-3,1-propanediy))bis(N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,3,5-triazine- 2,4,6-triamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 119 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
Remarks: The product has low solubility in the test medium.
An aqueous dispersion was tested.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7.3 mg/l
Exposure time: 24 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.432 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.37 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not accumulate in organisms.

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Mobility in soil

Product:

Mobility : Remarks: Not expected to adsorb on soil.

Remarks: The product is insoluble and sinks in water.

Other adverse effects

Product:

Additional ecological information : Should not be released into the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : This substance, when discarded or disposed of is not specifically listed as a hazardous waste in Federal regulations. However, it could be hazardous if it is considered toxic, corrosive, ignitable or reactive according to Federal definitions (40 CFR 261). Additionally, it could be designated as hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact or mixing may have occurred, check 40 CFR 261 to determine whether it is a hazardous waste. The transportation, storage, treatment and disposal of this waste material must be conducted in accordance with all applicable federal, state and local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

49 CFR Road

Not regulated as a dangerous good

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Special precautions for user

Remarks : Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

SECTION 15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.


TSCA list

Borealis certifies that all chemical substances in this shipment comply with all applicable rules or orders under TSCA and that Borealis is not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average

Borealis GmbH | Trabrennstasse 6-8 | 1020 Vienna | Austria
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333
FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Sources of key data used to compile the Material Safety Data Sheet : Safety data sheets of raw material suppliers.
Revision Date : 02/10/2026

SAFETY DATA SHEET

EG2402SYU

Version 4.1

Revision Date 02/10/2026

Former date 02/10/2026

Disclaimer

Recycled plastics are subject to material inconsistencies. Borealis GmbH makes no warranties which extend beyond the description contained herein and to the best of our knowledge, the information is accurate and reliable as of the date of publication. Because of the multitude of possible influences during the use and application of our products, the information included does not release customers and users from the obligation to examine and test them carefully. Please note that nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose as Borealis GmbH do not know the origin of the product. Where necessary, the customer is recommended to obtain a feedstock release from the customer. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of any Borealis GmbH product in conjunction with any other products and/or materials. The information contained herein relates exclusively to our products when not used in conjunction with any other material unless as specifically provided for in the test methods stated above. The product(s) mentioned herein are not intended to be used for food contact, drinking water contact, medical, pharmaceutical or healthcare applications and we do not support their use for such applications. Otherwise, our General Terms and Conditions of Sale apply.

US / EN