

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ETBE

REACH Registration Number : 01-2119452785-29-XXXX

Substance name : tert-Butyl ethyl ether

EC-No. : 211-309-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Raw material in chemical industry, Manufacture, Formulation, Distribution, Fuel use - Industrial, Fuel use - Professional, Fuel use - Consumer

1.3 Details of the supplier of the safety data sheet

Manufacturer : Borealis AB
S-444 86 Stenungsund, Sweden
Telephone: +46 303 86000

Supplier : Borealis AG
Trabrennstrasse 6-8, 1020 Vienna, Austria
Telephone: +43 1 22400 0

E-mail address : sds@borealisgroup.com

1.4 Emergency telephone number

||+44 (0) 1235 239 670 (NCEC Carechem 24)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : tert-Butyl ethyl ether

EC-No. : 211-309-7

Components

Chemical name	CAS-No. EC-No.	Concentration (%) w/w)	M-Factor, SCL, ATE
2-Ethoxy-2-methylpropane	637-92-3 211-309-7	> 95	
ethanol	64-17-5 200-578-6	0 - 5	
tert-butyl methyl ether	1634-04-4 216-653-1	0 - 5	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Move out of dangerous area.
Remove contaminated clothing and shoes.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Remove victim from exposure and then have him lie down in the recovery position.
Do not leave the victim unattended.
Keep patient warm and at rest.

If inhaled : Seek medical advice immediately.
If breathing is difficult, give oxygen.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Wash off immediately with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention if irritation develops and persists.

In case of eye contact : Rinse thoroughly with plenty of water, also under the eyelids.
If easy to do, remove contact lens, if worn.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Seek medical advice immediately.

If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may cause central nervous system effects.
Inhalation may provoke the following symptoms:
Breathing difficulties
Fever
Shortness of breath
Suffocation
Cough
Headache

Ingestion may provoke the following symptoms:
Dizziness
Fatigue
Drowsiness
Weakness
Lack of coordination

Symptoms may be delayed.

Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : In case of ingestion, the stomach should be emptied by gastric lavage under qualified medical supervision.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder
Carbon dioxide (CO₂)
Alcohol-resistant foam
Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Vapours may form explosive mixtures with air.
Flash back possible over considerable distance.
Risk of explosion.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

5.3 Advice for firefighters

Special protective equipment : Wear self-contained breathing apparatus and protective suit.
for firefighters

Further information : Keep people away from and upwind of spill/leak.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.
Avoid breathing vapours, mist or gas.
Ensure adequate ventilation, especially in confined areas.
Keep people away from and upwind of spill/leak.
Eliminate all ignition sources if safe to do so.
See chapter 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so.
Prevent product from entering environment and drains.
If major spillage occurs, contact the proper local authorities.
Do not allow material to contaminate ground water system.
Evaporates.

6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Use antispark tools (e.g. aluminium, plastic) to pick up the material.
Wipe up with absorbent material (e.g. cloth, fleece).

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Refill and handle product only in closed system.
Do not use in areas without adequate ventilation.
Ensure that eyewash stations and safety showers are close to the workstation location.
Avoid exposure - obtain special instructions before use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Advice on protection against fire and explosion : Take precautionary measures against static discharges. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Electrical equipment should be protected to the appropriate standard. Ensure adequate ventilation. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : Keep away from combustible material.
Keep away from incompatible materials.
See chapter 10.

Packaging material : Suitable material: Carbon steel

7.3 Specific end use(s)

Specific use(s) : Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanol	64-17-5	NGV	500 ppm 1.000 mg/m ³	SE AFS
Further information	Indicative short term limit value shall be used as a recommended maximum value and should not be exceeded			
		KGV	1.000 ppm 1.900 mg/m ³	SE AFS
Further information	Indicative short term limit value shall be used as a recommended maximum value and should not be exceeded			
tert-butyl methyl ether	1634-04-4	NGV	30 ppm 110 mg/m ³	SE AFS
		KGV	100 ppm 367 mg/m ³	SE AFS
		TWA	50 ppm 183,5 mg/m ³	2009/161/EU
Further information	Indicative			
		STEL	100 ppm 367 mg/m ³	2009/161/EU
Further information	Indicative			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Limit values in other countries:, Finland: ETBE, 5 ppm (8h, HTP 2009)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ETBE	Workers	Inhalation	Acute effects, Systemic	2800 mg/m3
	Workers	Skin contact	Long-term, Systemic	6767 mg/kg
	Workers	Inhalation	Long-term, Systemic	352 mg/m3
	Workers	Inhalation	Long-term, Local effects	105 mg/m3
	Consumers	Inhalation	Acute effects, Systemic	1680 mg/m3
	Consumers	Skin contact	Long-term, Systemic	4060 mg/kg
	Consumers	Inhalation	Long-term, Systemic	105 mg/m3
	Consumers	Ingestion	Long-term, Systemic	6 mg/kg
	Consumers	Inhalation	Long-term, Local effects	63 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ETBE	Fresh water	0,51 mg/l
	Marine water	0,017 mg/l
	Water	11 mg/l
Remarks:	Intermittent use/release	
	Fresh water sediment	0,62 mg/kg wet weight
	Marine sediment	0,017 mg/kg wet weight
	Soil	0,24 mg/kg wet weight
	Sewage treatment plant	12,5 mg/l

8.2 Exposure controls

Engineering measures

Application in a closed system
Provide adequate ventilation.
Use personal protective equipment.

Personal protective equipment

Eye protection : Wear goggles and if needed face-shield.
Equipment should conform to EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 8 h
Material : Viton®
Break through time : > 8 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

- Remarks : Wear suitable gloves:
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Gloves must be rinsed thoroughly after use. or
- Skin and body protection : Wear suitable protective clothing and rubber boots.
During handling operations:
Flame retardant protective clothing
- Respiratory protection : In case of insufficient ventilation: Respirator with A2 or ABEK filter or self-contained breathing apparatus.

Environmental exposure controls

- General advice : Prevent further leakage or spillage if safe to do so. Prevent product from entering environment and drains. If major spillage occurs, contact the proper local authorities. Do not allow material to contaminate ground water system. Evaporates.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : pale yellowish
- Odour : ether-like
- Odour Threshold : 13 ppb
- Melting point : -94 °C
- Boiling point : 73,1 °C
- Flammability : Highly flammable.
- Upper explosion limit / Upper flammability limit : 6 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Lower explosion limit / Lower flammability limit	: 1 %(V)
Flash point	: -19 °C
Decomposition temperature	: Heating or fire can release toxic and irritating gases.
pH	: ca. 6,4 Method: ASTM D6423
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 0,53 mm ² /s (20 °C) 0,47 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: 16,4 g/l (20 °C)
Partition coefficient: n-octanol/water	: log Pow: 1,48 (20 °C)
Vapour pressure	: 170 hPa (25 °C)
Relative density	: 0,75 (15 °C)
Density	: 750 g/cm ³
Relative vapour density	: ca. 3,5 (15 °C) (Air = 1.0)
Particle characteristics	
Particle Size Distribution	: Not applicable

9.2 Other information

Explosives	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Self-ignition	: 392 °C 1.003,4 - 1.009,2 hPa
Evaporation rate	: No data available
Molecular weight	: 102,17 g/mol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.
Reacts with air to form peroxides.
Flammable gases may be released if in contact with the following:
Strong acids

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents
Strong acids
Strong bases
Oxygen
Air

10.6 Hazardous decomposition products

Carbon monoxide (CO)
Toxic fumes

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50: > 2.003 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,88 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

Acute toxicity (other routes of administration) :
Remarks: No data available

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

Exposure routes : Inhalation
Remarks : No data available

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Product:

Genotoxicity in vitro

: Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative
GLP: yes

: Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Genotoxicity in vivo

: Test Type: in vivo assay
Species: Mouse
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Species : Rat, male and female
Application Route : Oral
NOAEC : 550 mg/kg bw/d

Species : Rat, male
Application Route : Inhalation
NOAEC : 1.500 ppm

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Species: Rat
Application Route: Ingestion
NOAEL: 1000 mg/kg bw/day,
Method: OECD Test Guideline 416

Effects on foetal development : Species: Rat
Application Route: Oral
1000 mg/kg bw/d
Number of exposures: 7d/w
Test period: 15 d
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Species: Rat
Application Route: Oral
1000 mg/kg bw/d
300 mg/kg bw/d
Method: OECD Test Guideline 414

Species: Rat
Application Route: Oral
500 mg/kg bw/d
Method: OECD Test Guideline 414

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

Species : Rat, male
NOAEL : 121 mg/kg
Application Route : Oral
Exposure time : 730 d
Method : OECD Test Guideline 453

Species : Rat, male and female
NOAEC : 2,1 mg/l
Application Route : inhalation (vapour)
Exposure time : 730 d
Method : OECD Test Guideline 453

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Experience with human exposure

Product:

General Information : Exposure to the vapour may result in lowering of consciousness.
Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Neurological effects

Product:

Inhalation may cause central nervous system effects.

Further information

Product:

Remarks : Prolonged skin contact may defat the skin and produce dermatitis.
Components of the product may be absorbed into the body by inhalation and ingestion.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 (guppy (*Poecilia reticulata*)): > 974 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: no
Remarks: Fresh water

LC50 (tidewater silverside (*Menidia beryllina*)): > 57,4 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: no
Remarks: Read-across (Analogy)
Marine water

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 110 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

aquatic invertebrates

Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes
Remarks: Fresh water

EC50 (*Americamysis bahia* (shrimp)): 37 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: EPA OTS 797.1930
Remarks: Marine water

Toxicity to algae/aquatic plants

: EC50 (*Pseudokirchneriella subcapitata* (green algae)): 1.100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes
Remarks: Fresh water

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 7,5 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes
Remarks: Fresh water

Toxicity to fish (Chronic toxicity)

: NOEC: 64 mg/l
Exposure time: 5 d
Species: *Danio rerio* (zebra fish)
Method: OECD Test Guideline 212

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

: NOEC: 5,1 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Test Type: flow-through test
Method: EPA OPPTS 850.1300
Remarks: Read-across (Analogy)
Fresh water

NOEC: 1,7 mg/l
Exposure time: 28 d
Species: *Americamysis bahia* (shrimp)
Test Type: flow-through test
Method: EPA OPPTS 850.1350
Remarks: Read-across (Analogy)
Marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Toxicity to microorganisms : NOEC (*Pseudomonas putida*): 12,5 mg/l
Exposure time: 16 h
Test Type: Respiration inhibition
Method: ISO 10712
GLP:
Remarks: Read-across (Analogy)
Fresh water

12.2 Persistence and degradability

Product:

Biodegradability : activated sludge, adapted
Biodegradation: 6,6 %
Exposure time: 7 d
Method: OECD Test Guideline 301D

Test Type: anaerobic
Water
Biodegradation: 0 %
Exposure time: 244 d

Soil
Kinetic:
151 d: 66 %

Remarks: Not readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No experimental BCF value is available.
Bioaccumulation not expected: Partition coefficient (n-octanol/water) $\log P_{ow} < 3$.

12.4 Mobility in soil

Product:

Mobility : Medium: Air
Remarks: 96,2%

Medium: Water
Remarks: 3,7%

Medium: Soil
Remarks: 0,1%, Partition coefficient (n-octanol/water) $\log K_{ow} < 3$.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Distribution among environmental compartments : Remarks: The product evaporates readily to air., Not expected to adsorb on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Environmental fate and pathways : Photodegradable.

Additional ecological information : No known effect.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Dispose of as hazardous waste in compliance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1179

IMDG : UN 1179

14.2 UN proper shipping name

ADR : ETHYL BUTYL ETHER

IMDG : ETHYL BUTYL ETHER

14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-D

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks :
SDS: No specific instructions needed.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Ship type : 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Pollution category : Y

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 40, 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

FLAMMABLE LIQUIDS

Other regulations:

No data available

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

SE AFS : Sweden. Occupational Exposure Limit Values

2009/161/EU / TWA : Limit Value - eight hours

2009/161/EU / STEL : Short term exposure limit

SE AFS / NGV : Time Weighted Average

SE AFS / KGV : Short Term Exposure Limit

Further information

Other information : Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Issuer : Borealis, Group Product Stewardship / Mikaela Eriksson.

Sources of key data used to compile the Safety Data Sheet : Chemical Safety Report, 2-ethoxy-2-methylpropane (ETBE), 2014
Information taken from reference works and the literature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

Annex: Exposure Scenarios

Table of Contents

Number	Title
ES1	Manufacture, Manufacture of substance
ES2	Formulation or re-packing, Formulation & (re)packing of substances and mixtures
ES3	Use at industrial sites, Distribution of substance
ES4	Use at industrial sites, Use in fuel
ES5	Widespread use by professional workers, Use in fuel
ES6	Consumer use, Use in fuels

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES1: Manufacture of substance

1.1. Title section

Structured Short Title	: Manufacture, Manufacture of substance
-------------------------------	---

Environment		
CS1	Manufacture of substance	ERC1
Worker		
CS2	General measures	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15
CS3	General exposures (closed systems)	PROC1
CS4	General exposures (closed systems), With sample collection	PROC2
CS5	General exposures (closed systems), Use in contained batch processes, With sample collection	PROC3
CS6	General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers	PROC4
CS7	Process sampling, Dedicated facility	PROC8b
CS8	Laboratory activities	PROC15
CS9	Bulk transfers, Non-dedicated facility	PROC8a
CS10	Bulk transfers, Dedicated facility	PROC8b
CS11	Equipment cleaning and maintenance, Non-dedicated facility	PROC8a
CS12	Storage, General exposures (closed systems)	PROC1
CS13	Storage, General exposures (closed systems), With sample collection	PROC2

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Manufacture of the substance (ERC1)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Daily amount per site : 905000 kg

Annual amount per site : 271600 ton(s)/year

Release type : Continuous release

Emission days : 300

Technical and organisational conditions and measures

No air emission controls required; required removal efficiency is 0%.

Soil emission controls are not applicable as there is no direct release to soil.

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):

Water - minimum efficiency of > 99 %

Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to sewage treatment plant

STP type : Onsite Sewage Treatment Plant

STP effluent : 2.000 m³/d

STP type : Municipal Sewage Treatment Plant

STP effluent : 2.000 m³/d

Estimated substance removal from wastewater via domestic sewage treatment:

Water - minimum efficiency of 99 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.
External recovery and recycling of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local freshwater dilution factor : 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

1.2.2. Control of worker exposure: General measures

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Use as laboratory reagent (PROC15)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Common practices vary across sites thus conservative process release estimates used.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is implemented

1.2.3. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

No other specific measures identified.

1.2.4. Control of worker exposure: General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

1.2.5. Control of worker exposure: General exposures (closed systems), Use in contained batch processes, With sample collection Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

1.2.6. Control of worker exposure: General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers Chemical production where opportunity for exposure arises (PROC4)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

1.2.7. Control of worker exposure: Process sampling, Dedicated facility Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Technical and organisational conditions and measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Provide extract ventilation to points where emissions occur.

1.2.8. Control of worker exposure: Laboratory activities

Use as laboratory reagent (PROC15)

Technical and organisational conditions and measures

Handle in a fume cupboard or under extract ventilation.

1.2.9. Control of worker exposure: Bulk transfers, Non-dedicated facility

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Transfer via enclosed lines.
Clear transfer lines prior to de-coupling.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

1.2.10. Control of worker exposure: Bulk transfers, Dedicated facility

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity 4 h

Technical and organisational conditions and measures

Transfer via enclosed lines.
Clear transfer lines prior to de-coupling.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

1.2.11. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 1 h

Technical and organisational conditions and measures

Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

1.2.12. Control of worker exposure: Storage, General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

1.2.13. Control of worker exposure: Storage, General exposures (closed systems), With sample collection

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Manufacture of the substance (ERC1)

Release route	Release rate	Release estimation method
---------------	--------------	---------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Air	0,005	ESVOC SPERC 1.1.v1
Water	0,01	ESVOC SPERC 1.1.v1
Soil	0,000	ESVOC SPERC 1.1.v1

Compartment	Exposure level	RCR
Sewage treatment plant	0,0115 mg/L (EUSES)	0,001
Surface water	0,0016 mg/L (EUSES)	0,003
Freshwater sediment	0,00192 mg/kg wet weight (EUSES)	0,003
Marine water	0,000184 mg/L (EUSES)	0,011
Marine sediment	0,00022 mg/kg wet weight (EUSES)	0,011
Agricultural soil	0,200 mg/kg wet weight (EUSES)	0,833
Grassland	0,207 mg/kg wet weight (EUSES)	0,863

Additional information on exposure estimation

Risk from environmental exposure is driven by soil.

1.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	
dermal			0,03 mg/kg/d	< 0,001	

1.3.4. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	45 mg/m ³	< 0,43	
inhalative		short-term	290 mg/m ³	0,11	
dermal			0,82 mg/kg/d	< 0,001	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

1.3.5. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,2	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,069 mg/kg/d	< 0,001	

1.3.6. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	43 mg/m ³	0,4	
inhalative		short-term	170 mg/m ³	0,06	
dermal			0,69 mg/kg/d	< 0,001	

1.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	32 mg/m ³	0,3	
inhalative		short-term	120 mg/m ³	0,05	
dermal			0,69 mg/kg/d	< 0,001	

1.3.8. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,2	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,03 mg/kg/d	< 0,001	

1.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	100 mg/m ³	0,95	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

inhalative		short-term	180 mg/m ³	0,06	
dermal			8,2 mg/kg/d	0,001	

1.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	100 mg/m ³	0,95	
inhalative		short-term	180 mg/m ³	0,06	
dermal			8,2 mg/kg/d	0,001	

1.3.11. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,2	
inhalative		short-term	420 mg/m ³	0,15	
dermal			2,7 mg/kg/d	< 0,001	

1.3.12. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	
dermal			0,03 mg/kg/d	< 0,001	

1.3.13. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	6,3 mg/m ³	0,06	
inhalative		short-term	43 mg/m ³	0,02	
dermal			0,82 mg/kg/d	< 0,001	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Health

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES2: Formulation & (re)packing of substances and mixtures

2.1. Title section

Structured Short Title	: Formulation or re-packing, Formulation & (re)packing of substances and mixtures
-------------------------------	---

Environment		
CS1	Environment	ERC2
Worker		
CS2	Formulation & (re)packing of substances and mixtures	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
CS3	General exposures (closed systems)	PROC1
CS4	General exposures (closed systems), With sample collection	PROC2
CS5	General exposures (closed systems), Use in contained batch processes, With sample collection	PROC3
CS6	General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers	PROC4
CS7	General exposures (open systems), Batch processes at elevated temperatures, With sample collection	PROC3
CS8	Process sampling, Dedicated facility	PROC3
CS9	Laboratory activities	PROC15
CS10	Bulk transfers, Dedicated facility	PROC8b
CS11	Mixing operations (open systems), Batch process	PROC5
CS12	Manual, Transfer from/pouring from containers, Non-dedicated facility	PROC8a
CS13	Drum/batch transfers, Dedicated facility	PROC8b
CS14	Drum and small package filling, Dedicated facility	PROC9
CS15	Equipment cleaning and maintenance, Non-dedicated facility	PROC8a

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

CS16	Storage, General exposures (closed systems)	PROC1
CS17	Storage, General exposures (closed systems), With sample collection	PROC2

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Vapour pressure	: Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 150000 kg
Annual amount per site	: 45050 ton(s)/year
Release type	: Continuous release
Emission days	: 300
Technical and organisational conditions and measures	
No air emission controls required; required removal efficiency is 0%.	
Soil emission controls are not applicable as there is no direct release to soil.	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): Water - minimum efficiency of > 99 %	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP effluent	: 2.000 m³/d
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m³/d
Estimated substance removal from wastewater via domestic sewage treatment: Water - minimum efficiency of 99 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Conditions and measures related to treatment of waste (including article waste)

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.
External recovery and recycling of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local freshwater dilution factor : 10

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

2.2.2. Control of worker exposure: Formulation & (re)packing of substances and mixtures
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Use as laboratory reagent (PROC15)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Common practices vary across sites thus conservative process release estimates used.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Temperature : Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is implemented

2.2.3. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

2.2.4. Control of worker exposure: General exposures (closed systems), With sample collection

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

2.2.5. Control of worker exposure: General exposures (closed systems), Use in contained batch processes, With sample collection

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

2.2.6. Control of worker exposure: General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers

Chemical production where opportunity for exposure arises (PROC4)

Technical and organisational conditions and measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Provide extract ventilation to points where emissions occur.

2.2.7. Control of worker exposure: General exposures (open systems), Batch processes at elevated temperatures, With sample collection

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.
Formulate in enclosed or ventilated mixing vessels.

2.2.8. Control of worker exposure: Process sampling, Dedicated facility

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

2.2.9. Control of worker exposure: Laboratory activities

Use as laboratory reagent (PROC15)

Technical and organisational conditions and measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

2.2.10. Control of worker exposure: Bulk transfers, Dedicated facility

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Technical and organisational conditions and measures

Provide extract ventilation to material transfer points and other openings.

2.2.11. Control of worker exposure: Mixing operations (open systems), Batch process

Mixing or blending in batch processes (PROC5)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

2.2.12. Control of worker exposure: Manual, Transfer from/pouring from containers, Non-dedicated facility

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Ensure material transfers are under containment or extract ventilation.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

2.2.13. Control of worker exposure: Drum/batch transfers, Dedicated facility

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Technical and organisational conditions and measures

Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.
Use drum pumps.

2.2.14. Control of worker exposure: Drum and small package filling, Dedicated facility

Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Technical and organisational conditions and measures

Fill containers/cans at dedicated fill points supplied with local extract ventilation.

2.2.15. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 1 h

Technical and organisational conditions and measures

Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

2.2.16. Control of worker exposure: Storage, General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

2.2.17. Control of worker exposure: Storage, General exposures (closed systems), With sample collection

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 1 h

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Release route	Release rate	Release estimation method
Air	0,025	ESVOC SPERC 1.1.v1
Water	0,005	ESVOC SPERC 1.1.v1
Soil	0,000	ESVOC SPERC 1.1.v1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Compartment	Exposure level	RCR
Sewage treatment plant	0,01 mg/L (EUSES)	0,001
Surface water	0,00144 mg/L (EUSES)	0,003
Freshwater sediment	0,00174 mg/kg wet weight (EUSES)	0,003
Marine water	0,000168 mg/L (EUSES)	0,010
Marine sediment	0,000201 mg/kg wet weight (EUSES)	0,010
Agricultural soil	0,118 mg/kg wet weight (EUSES)	0,491
Grassland	0,129 mg/kg wet weight (EUSES)	0,537

Additional information on exposure estimation

Risk from environmental exposure is driven by soil.

2.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	
dermal			0,03 mg/kg/d	< 0,001	

2.3.4. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	45 mg/m ³	0,13	
inhalative		short-term	290 mg/m ³	0,11	
dermal			0,82 mg/kg/d	< 0,001	

2.3.5. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure	Exposure level	RCR	Remarks
----------------	---------------	----------	----------------	-----	---------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

		indicator			
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,07 mg/kg/d	< 0,001	

2.3.6. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	43 mg/m ³	0,12	
inhalative		short-term	170 mg/m ³	0,06	
dermal			0,69 mg/kg/d	< 0,001	

2.3.7. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,07 mg/kg/d	< 0,001	

2.3.8. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,07 mg/kg/d	< 0,001	

2.3.9. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	250 mg/m ³	0,09	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

dermal			0,34 mg/kg/d	< 0,001	
--------	--	--	--------------	---------	--

2.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	32 mg/m ³	0,09	
inhalative		short-term	120 mg/m ³	0,05	
dermal			0,69 mg/kg/d	< 0,001	

2.3.11. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	420 mg/m ³	0,15	
dermal			0,82 mg/kg/d	< 0,001	

2.3.12. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	420 mg/m ³	0,15	
dermal			0,82 mg/kg/d	< 0,001	

2.3.13. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	32 mg/m ³	0,09	
inhalative		short-term	120 mg/m ³	0,05	
dermal			0,07 mg/kg/d	< 0,001	

2.3.14. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	85 mg/m ³	0,24	
inhalative		short-term	340 mg/m ³	0,12	
dermal			0,69 mg/kg/d	< 0,001	

2.3.15. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	420 mg/m ³	0,15	
dermal			2,7 mg/kg/d	< 0,001	

2.3.16. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	
dermal			0,03 mg/kg/d	< 0,001	

2.3.17. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	420 mg/m ³	0,15	
dermal			0,27 mg/kg/d	< 0,001	

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Further details on scaling and control technologies are provided in SpERC factsheet
(<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES3: Distribution of substance

3.1. Title section

Structured Short Title	: Use at industrial sites, Distribution of substance
-------------------------------	--

Environment		
CS1	Environment, transport	ERC1, ERC2
CS2	Environment, Storage	ERC1, ERC2
Worker		
CS3	General measures	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15
CS4	General exposures (closed systems)	PROC1
CS5	General exposures (closed systems), With sample collection	PROC2
CS6	General exposures (closed systems), Use in contained batch processes, With sample collection	PROC3
CS7	General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers	PROC4
CS8	Process sampling	PROC3
CS9	Laboratory activities	PROC15
CS10	Bulk closed loading and unloading, Dedicated facility	PROC8b
CS11	Bulk open loading and unloading, Non-dedicated facility	PROC8a
CS12	Drum and small package filling, Dedicated facility	PROC9
CS13	Equipment cleaning and maintenance, Non-dedicated facility	PROC8a
CS14	Storage, General exposures (closed systems)	PROC1
CS15	Storage, General exposures (closed systems), With sample collection	PROC2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Manufacture of the substance (ERC1) / Formulation into mixture (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Vapour pressure	: Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 49300 kg
Annual amount per site	: 18020 ton(s)/year
Release type	: Continuous release
Emission days	: 365
Technical and organisational conditions and measures	
No air emission controls required; required removal efficiency is 0%.	
Soil emission controls are not applicable as there is no direct release to soil.	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): Water - minimum efficiency of > 97 %	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Estimated substance removal from wastewater via domestic sewage treatment: Water - minimum efficiency of 97 %	
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

applicable local and/or national regulations.	
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
None.	

3.2.2. Control of environmental exposure: Manufacture of the substance (ERC1) / Formulation into mixture (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Vapour pressure	: Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
Amount used, frequency and duration of use (or from service life)	
Annual amount per site	: 900000 ton(s)/year
Release type	: Continuous release
Emission days	: 365
Technical and organisational conditions and measures	
No air emission controls required; required removal efficiency is 0%.	
Soil emission controls are not applicable as there is no direct release to soil.	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): Water - minimum efficiency of > 97 %	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m³/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Estimated substance removal from wastewater via domestic sewage treatment:
Water - minimum efficiency of 97 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.
External recovery and recycling of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local freshwater dilution factor : 10

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

3.2.3. Control of worker exposure: General measures

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Use as laboratory reagent (PROC15)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Common practices vary across sites thus conservative process release estimates used.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is implemented

3.2.4. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

3.2.5. Control of worker exposure: General exposures (closed systems), With sample collection

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

3.2.6. Control of worker exposure: General exposures (closed systems), Use in contained batch processes, With sample collection

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.

3.2.7. Control of worker exposure: General exposures (open systems), Batch process, With sample collection, Filling of equipment from drums or containers

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Chemical production where opportunity for exposure arises (PROC4)

Technical and organisational conditions and measures

Provide extract ventilation to points where emissions occur.
Ensure samples are obtained under containment or extract ventilation.

3.2.8. Control of worker exposure: Process sampling

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 15 min

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

3.2.9. Control of worker exposure: Laboratory activities

Use as laboratory reagent (PROC15)

Technical and organisational conditions and measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

3.2.10. Control of worker exposure: Bulk closed loading and unloading, Dedicated facility

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 1 h

Technical and organisational conditions and measures

Ensure operation is undertaken outdoors.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

3.2.11. Control of worker exposure: Bulk open loading and unloading, Non-dedicated facility

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 1 h

Technical and organisational conditions and measures

Ensure material transfers are under containment or extract ventilation.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

3.2.12. Control of worker exposure: Drum and small package filling, Dedicated facility Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Technical and organisational conditions and measures

Fill containers/cans at dedicated fill points supplied with local extract ventilation.

3.2.13. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

3.2.14. Control of worker exposure: Storage, General exposures (closed systems) Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

3.2.15. Control of worker exposure: Storage, General exposures (closed systems), With sample collection

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)	
Duration	: Duration of the activity < 1 h
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140 with Type A filter or better.	

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Manufacture of the substance (ERC1) / Formulation into mixture (ERC2)

Release route	Release rate	Release estimation method
Air	0,000	ESVOC SPERC 3.22a.v1
Water	0,000	ESVOC SPERC 3.22a.v1
Soil	0,000	ESVOC SPERC 3.22a.v1

Compartment	Exposure level	RCR
Sewage treatment plant	0,00938 mg/L (EUSES)	0,001
Surface water	0,00162 mg/L (EUSES)	0,003
Freshwater sediment	0,00166 mg/kg wet weight (EUSES)	0,003
Marine water	0,000162 mg/L (EUSES)	0,010
Marine sediment	0,000194 mg/kg wet weight (EUSES)	0,010
Agricultural soil	0,00296 mg/kg wet weight (EUSES)	0,012
Grassland	0,000702 mg/kg wet weight (EUSES)	0,003

3.3.2. Environmental release and exposure: Manufacture of the substance (ERC1) / Formulation into mixture (ERC2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Release route	Release rate	Release estimation method
Air	0 kg/day	ESVOC SPERC 3.22a.v1
Water	8,4 kg/day	ESVOC SPERC 3.22a.v1
Soil	0 kg/day	ESVOC SPERC 3.22a.v1

Compartment	Exposure level	RCR
Sewage treatment plant	0,00959 mg/L (EUSES)	0,001
Surface water	0,0014 mg/L (EUSES)	0,003
Freshwater sediment	0,00169 mg/kg wet weight (EUSES)	0,003
Marine water	0,000164 mg/L (EUSES)	0,010
Marine sediment	0,000196 mg/kg wet weight (EUSES)	0,010
Agricultural soil	0,0207 mg/kg wet weight (EUSES)	0,086
Grassland	0,00153 mg/kg wet weight (EUSES)	0,006

Additional information on exposure estimation

Risk from environmental exposure is driven by soil.

3.3.4. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	
dermal			0,03 mg/kg/d	< 0,001	

3.3.5. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	45 mg/m ³	0,13	
inhalative		short-term	290 mg/m ³	0,11	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

dermal			0,82 mg/kg/d	< 0,001	
--------	--	--	--------------	---------	--

3.3.6. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	85 mg/m ³	0,03	
dermal			0,07 mg/kg/d	< 0,001	

3.3.7. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	43 mg/m ³	0,12	
inhalative		short-term	170 mg/m ³	0,06	
dermal			0,69 mg/kg/d	< 0,001	

3.3.8. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	850 mg/m ³	0,3	
dermal			0,068 mg/kg/d	< 0,001	

3.3.9. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	250 mg/m ³	0,09	
dermal			0,34 mg/kg/d	< 0,001	

3.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	89 mg/m ³	0,25	
inhalative		short-term	1,7 g/m ³	0,64	
dermal			2,7 mg/kg/d	< 0,001	

3.3.11. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	420 mg/m ³	0,15	
dermal			0,27 mg/kg/d	< 0,001	

3.3.12. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	85 mg/m ³	0,24	
inhalative		short-term	340 mg/m ³	0,12	
dermal			0,69 mg/kg/d	< 0,001	

3.3.13. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	420 mg/m ³	0,15	
dermal			8,2 mg/kg/d	0,001	

3.3.14. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,042 mg/m ³	< 0,01	
inhalative		short-term	0,17 mg/m ³	< 0,01	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

dermal			0,03 mg/kg/d	< 0,001	
--------	--	--	--------------	---------	--

3.3.15. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	21 mg/m ³	0,06	
inhalative		short-term	420 mg/m ³	0,15	
dermal			0,27 mg/kg/d	< 0,001	

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES4: Use in fuel

4.1. Title section

Structured Short Title	: Use at industrial sites, Use in fuel
-------------------------------	--

Environment		
CS1	Environment	ERC6b
Worker		
CS2	General measures applicable to all activities	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16
CS3	Bulk transfers, Batch process, With sample collection, Filling of equipment from drums or containers	PROC8b
CS4	Drum/batch transfers, Filling of equipment from drums or containers, Bulk transfers, Dedicated facility	PROC8b
CS5	General exposures (closed systems)	PROC1
CS6	General exposures (closed systems), With sample collection	PROC2
CS7	General exposures (closed systems), Use in contained batch processes, With sample collection	PROC3
CS8	Use in fuel, Closed systems	PROC16
CS9	Batch process, Closed systems	PROC3
CS10	Equipment cleaning and maintenance, Non-dedicated facility, e.g. fuel pump repair indoor	PROC8a
CS11	Storage, General exposures (closed systems)	PROC1
CS12	Storage, General exposures (closed systems), With sample collection	PROC2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Use of reactive processing aid at industrial site (no inclusion into or onto article) (ERC6b)

Product (article) characteristics	
Vapour pressure	: Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 51400 kg
Annual amount per site	: 18020 ton(s)/year
Release type	: Continuous release
Emission days	: 350
Technical and organisational conditions and measures	
No air emission controls required; required removal efficiency is 0%.	
Soil emission controls are not applicable as there is no direct release to soil.	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): Water - minimum efficiency of > 95 %	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Estimated substance removal from wastewater via domestic sewage treatment: Water - minimum efficiency of 95 %	
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: This substance is consumed during use and no waste of the substance is generated.
Other conditions affecting environmental exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Local freshwater dilution factor : 10

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

4.2.2. Control of worker exposure: General measures applicable to all activities

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Use of fuels (PROC16)

Product (article) characteristics

Covers concentrations up to 15 %

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Common practices vary across sites thus conservative process release estimates used.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is implemented

4.2.3. Control of worker exposure: Bulk transfers, Batch process, With sample collection, Filling of equipment from drums or containers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Use vapour recovery units when necessary.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

4.2.4. Control of worker exposure: Drum/batch transfers, Filling of equipment from drums or containers, Bulk transfers, Dedicated facility
Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Technical and organisational conditions and measures

Use drum pumps.

4.2.5. Control of worker exposure: General exposures (closed systems)
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

4.2.6. Control of worker exposure: General exposures (closed systems), With sample collection
Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Technical and organisational conditions and measures

Provide extract ventilation to material transfer points and other openings.

4.2.7. Control of worker exposure: General exposures (closed systems), Use in contained batch processes, With sample collection
Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Provide extract ventilation to points where emissions occur.

4.2.8. Control of worker exposure: Use in fuel, Closed systems Use of fuels (PROC16)

Technical and organisational conditions and measures

No other specific measures identified.

4.2.9. Control of worker exposure: Batch process, Closed systems Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide extract ventilation to material transfer points and other openings.

4.2.10. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility, e.g. fuel pump repair indoor Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Drain down and flush system prior to equipment break-in or maintenance.

4.2.11. Control of worker exposure: Storage, General exposures (closed systems) Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

4.2.12. Control of worker exposure: Storage, General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Technical and organisational conditions and measures

Ensure operation is undertaken outdoors.

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Use of reactive processing aid at industrial site (no inclusion into or onto article) (ERC6b)

Release route	Release rate	Release estimation method
Air	0,003	
Water	0,000	
Soil	0	

Compartment	Exposure level	RCR
Sewage treatment plant	0,00909 mg/L (EUSES)	0,001
Surface water	0,00135 mg/L (EUSES)	0,003
Freshwater sediment	0,00163 mg/L (EUSES)	0,003
Marine water	0,000159 mg/L (EUSES)	0,010
Marine sediment	0,00019 mg/kg wet weight (EUSES)	0,010
Agricultural soil	0,0058 mg/kg wet weight (EUSES)	0,024
Grassland	0,00511 mg/kg wet weight (EUSES)	0,021

Additional information on exposure estimation

Risk from environmental exposure is driven by soil.

4.3.3. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	46 mg/m ³	0,13	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

inhalative		short-term	300 mg/m ³	0,11	
dermal			4,9 mg/kg/d	< 0,001	

4.3.4. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	77 mg/m ³	0,22	
inhalative		short-term	300 mg/m ³	0,11	
dermal			8,2 mg/kg/d	0,001	

4.3.5. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,025 mg/m ³	< 0,01	
inhalative		short-term	0,1 mg/m ³	< 0,01	
dermal			0,018 mg/kg/d	< 0,001	

4.3.6. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	6,3 mg/m ³	0,02	
inhalative		short-term	26 mg/m ³	0,01	
dermal			0,08 mg/kg/d	< 0,001	

4.3.7. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	13 mg/m ³	0,04	
inhalative		short-term	51 mg/m ³	0,02	
dermal			0,04 mg/kg/d	< 0,001	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

4.3.8. Worker exposure: Use of fuels (PROC16)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	64 mg/m ³	0,18	
inhalative		short-term	250 mg/m ³	0,09	
dermal			0,2 mg/kg/d	< 0,001	

4.3.9. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	13 mg/m ³	0,04	
inhalative		short-term	51 mg/m ³	0,02	
dermal			0,04 mg/kg/d	0,001	

4.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	38 mg/m ³	0,11	
inhalative		short-term	250 mg/m ³	0,09	
dermal			4,9 mg/kg/d	< 0,001	

4.3.11. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,025 mg/m ³	< 0,01	
inhalative		short-term	0,1 mg/m ³	< 0,01	
dermal			0,018 mg/kg/d	< 0,001	

4.3.12. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
----------------	---------------	--------------------	----------------	-----	---------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

inhalative		long-term	45 mg/m ³	0,13	
inhalative		short-term	170 mg/m ³	0,06	
dermal			0,82 mg/kg/d	< 0,001	

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES5: Use in fuel

5.1. Title section

Structured Short Title	: Widespread use by professional workers, Use in fuel
-------------------------------	---

Environment		
CS1	Environment	ERC8b, ERC8e
Worker		
CS2	General measures	PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC16
CS3	Bulk transfers, Batch process, Filling of equipment from drums or containers	PROC8b
CS4	Drum/batch transfers, Filling of equipment from drums or containers	PROC8b
CS5	Refuelling	PROC8b
CS6	General exposures (closed systems), With sample collection	PROC2
CS7	General exposures (closed systems), Use in contained batch processes, With sample collection	PROC3
CS8	Drum and small package filling, Dedicated facility	PROC9
CS9	Use of fuel, Closed systems	PROC16
CS10	Equipment cleaning and maintenance, Non-dedicated facility, e.g. fuel pump repair indoor	PROC8a
CS11	Equipment cleaning and maintenance, Non-dedicated facility, e.g. fuel pump repair outdoor	PROC8a
CS12	Storage, General exposures (closed systems)	PROC1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) (ERC8b) / Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8e)

Product (article) characteristics	
Vapour pressure	: Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure
Amount used, frequency and duration of use (or from service life)	
Daily amount for wide dispersive uses	: 4,94 kg
Annual amount per site	: 1,8 ton(s)/year
Release type	: Continuous release
Emission days	: 365
Technical and organisational conditions and measures	
No air emission controls required; required removal efficiency is 0%.	
Soil emission controls are not applicable as there is no direct release to soil.	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): Water - minimum efficiency of > 95 %	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Estimated substance removal from wastewater via domestic sewage treatment: Water - minimum efficiency of 95 %	
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Other conditions affecting environmental exposure

Local freshwater dilution factor : 10

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

5.2.2. Control of worker exposure: General measures

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Use of fuels (PROC16)

Product (article) characteristics

Covers concentrations up to 15 %

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Common practices vary across sites thus conservative process release estimates used.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is implemented

5.2.3. Control of worker exposure: Bulk transfers, Batch process, Filling of equipment from drums or containers

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Duration of the activity < 4 h
Technical and organisational conditions and measures	
Ensure operation is undertaken outdoors.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140 with Type A filter or better.	

5.2.4. Control of worker exposure: Drum/batch transfers, Filling of equipment from drums or containers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Technical and organisational conditions and measures	
Use vapour recovery units when necessary. Ensure material transfers are under containment or extract ventilation.	

5.2.5. Control of worker exposure: Refuelling

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Duration of the activity < 1 h
Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140 with Type A filter or better.	

5.2.6. Control of worker exposure: General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)	
---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Duration : Duration of the activity < 4 h

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

5.2.7. Control of worker exposure: General exposures (closed systems), Use in contained batch processes, With sample collection

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Technical and organisational conditions and measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

5.2.8. Control of worker exposure: Drum and small package filling, Dedicated facility Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Use drum pumps or carefully pour from container.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

5.2.9. Control of worker exposure: Use of fuel, Closed systems Use of fuels (PROC16)

Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Ensure operation is undertaken outdoors.

5.2.10. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility, e.g. fuel pump repair indoor Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Drain down system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

5.2.11. Control of worker exposure: Equipment cleaning and maintenance, Non-dedicated facility, e.g fuel pump repair outdoor

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)

Duration : Duration of the activity < 4 h

Technical and organisational conditions and measures

Drain down system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear a respirator conforming to EN140 with Type A filter or better.

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor

5.2.12. Control of worker exposure: Storage, General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

No other specific measures identified.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) (ERC8b) / Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8e)

Release route	Release rate	Release estimation method
Air	0,01	
Water	0,000	
Soil	0,000	

Compartment	Exposure level	RCR
Sewage treatment plant	0,00248 mg/L (EUSES)	0,000
Surface water	0,000692 mg/L (EUSES)	0,001
Freshwater sediment	0,000819 mg/kg wet weight (EUSES)	0,001
Marine water	0,0000933 mg/L (EUSES)	0,005
Marine sediment	0,00011 mg/kg wet weight (EUSES)	0,006
Agricultural soil	0,000908 mg/kg wet weight (EUSES)	0,004
Grassland	0,000667 mg/kg wet weight (EUSES)	0,003

Additional information on exposure estimation

Risk from environmental exposure is driven by soil.

5.3.3. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	260 mg/m ³	0,76	
inhalative		short-term	1,7 g/m ³	0,99	
dermal			4,9 mg/kg/d	< 0,001	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

5.3.4. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	120 mg/m ³	0,36	
inhalative		short-term	510 mg/m ³	0,28	
dermal			8,2 mg/kg/d	0,001	

5.3.5. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	38 mg/m ³	0,11	
inhalative		short-term	760 mg/m ³	0,43	
dermal			1,6 mg/kg/d	< 0,001	

5.3.6. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	77 mg/m ³	0,22	
inhalative		short-term	510 mg/m ³	0,28	
dermal			0,49 mg/kg/d	< 0,001	

5.3.7. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	77 mg/m ³	0,22	
inhalative		short-term	300 mg/m ³	0,17	
dermal			0,41 mg/kg/d	< 0,001	

5.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
----------------	---------------	--------------------	----------------	-----	---------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

inhalative		long-term	77 mg/m ³	0,22	
inhalative		short-term	510 mg/m ³	0,28	
dermal			2,4 mg/kg/d	< 0,001	

5.3.9. Worker exposure: Use of fuels (PROC16)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	89 mg/m ³	0,25	
inhalative		short-term	350 mg/m ³	0,2	
dermal			0,2 mg/kg/d	< 0,001	

5.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	150 mg/m ³	0,43	
inhalative		short-term	1,0 g/m ³	0,57	
dermal			4,9 mg/kg/d	< 0,001	

5.3.11. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	150 mg/m ³	0,43	
inhalative		short-term	1,0 g/m ³	0,57	
dermal			4,9 mg/kg/d	< 0,001	

5.3.12. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		long-term	0,025 mg/m ³	< 0,01	
inhalative		short-term	0,1 mg/m ³	< 0,01	
dermal			0,018 mg/kg/d	< 0,001	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment

Not applicable for wide dispersive uses.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

Health

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

ES6: Use in fuels

6.1. Title section

Structured Short Title	: Consumer use, Use in fuels
-------------------------------	------------------------------

Environment		
CS1	Environment	ERC8b, ERC8e
Consumer		
CS2	Use of fuel	PC13

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) (ERC8b) / Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8e)

Product (article) characteristics	
Covers concentrations up to 15	
Amount used, frequency and duration of use (or from service life)	
For each use event, covers use amounts up to	: 37,5 kg
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: This substance is consumed during use and no waste of the substance is generated.
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m³/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Other conditions affecting environmental exposure

Local freshwater dilution factor : 10

Local marine water dilution factor : 100

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

None.

6.2.2. Control of consumer exposure: Use of fuel Fuels (PC13)

Product (article) characteristics

Covers concentrations up to 15 %

Vapour pressure : Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used, frequency and duration of use (or from service life)

For each use event, covers use amounts up to : 37,5 kg

Use frequency : Covers use up to 150 times per year

Use frequency : Covers use up to 15 min/event

Other conditions affecting consumers exposure

Body parts exposed : Covers skin contact area up to 210 cm² (unless stated differently).

Indoor or outdoor use : Outdoor use

Temperature : Assumes use at not more than 20°C above ambient temperature.

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) (ERC8b) / Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8e)

Compartment	Exposure level	RCR
-------------	----------------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ETBE

Version 8.0

Revision Date: 04.08.2022

Former date: 03.07.2019

Sewage treatment plant	0,00248 mg/L	0,000
Surface water	0,000692 mg/L	0,001
Freshwater sediment	0,000819 mg/kg wet weight	0,001
Marine water	0,0000933 mg/L	0,005
Marine sediment	0,00011 mg/kg wet weight	0,006
Agricultural soil	0,000908 mg/kg wet weight	0,004
Grassland	0,000667 mg/kg wet weight	0,003

Additional information on exposure estimation

Risk from environmental exposure is driven by marine sediment.

6.3.2. Consumer exposure: Fuels (PC13)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative		short-term	29 mg/m ³	0,017	
inhalative		Chronic exposure	0,026 mg/m ³	0,000	
dermal	systemic	Chronic exposure	0,011 mg/kg bw/day	0,000	

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Health

No data available

Environment

Not applicable for wide dispersive uses.