

# PRODUCT DATA SHEET

## Post-Consumer Recyclate

# Purpolen™ PE FF-96

## High Density Polyethylene



Accelerating Action  
on Circularity

### Description

Purpolen™ PE FF-96 is a deep black polyethylene (PE) post-consumer recyclate supplied in pellet form. This product is an ideal PE used where sustainability and circularity matter. Purpolen™ PE FF-96 is a 100% post-consumer recyclate including a large part of recycled post-consumer plastic waste coming from pre-sorted municipal (household) waste. It is a part of EuCertPlast certificate according to European Standard EN15343:2007 (certificate available upon request).

Due to the nature of recyclates, some variation in colour can be observed between batches.

Good demoulding properties

Filtration: 100 µm

Available in homogenized 24-ton truckloads

### Applications

Purpolen™ PE FF-96 is intended for following applications:

Injection moulding applications

### Physical properties

Property	Typical value *	Unit	Test method
Density	955	kg/m <sup>3</sup>	ISO 1183
Melt flow rate (190 °C/2.16 kg)	1	g/10min	ISO 1133
Moisture content	<0.1	%	Moisture analyzer (infrared)
Ash content (950°C) <sup>1</sup>	<2	%	ISO 1172
Tensile modulus (1 mm/min)	900	MPa	ISO 527-2
Tensile stress at yield (50 mm/min)	22	MPa	ISO 527-2
Charpy impact strength, notched (23 °C)	15	kJ/m <sup>2</sup>	ISO 179-1/1eA

<sup>1</sup> Refers to filler content

\* Data should not be used for specification work

### Processing techniques

This product is easy to process with standard injection molding machines.

Following parameters should be used as a guideline:

Processing setting	Typical value/range
Melt temperature <sup>2</sup>	190 °C
Mould temperature <sup>3</sup>	35 °C
Holding pressure <sup>4</sup>	350 bar

<sup>2</sup> Range: 170 - 200 °C

<sup>3</sup> Range: 30 - 50 bar

<sup>4</sup> Range: 200- 500 °C

Purpolen™ is a trademark of the Borealis Group

## Post-Consumer Recyclate

# Purpolen™ PE FF-96

### Packaging and storage

Purpolen™ PE FF-96 should be stored in dry conditions at temperatures below 50°C and protected from UV-light. Improper storage can initiate degradation, which can result in odour generation and colour changes and can have negative effects on the physical properties of this product. The shelf life is a maximum of one year after production. The shelf life of a product can be extended after properties are re-testing selected material properties and verifying that the test results are still within the product specification. It is recommended to measure the moisture after longer storage periods prior to processing.

### Product compliance documents

Latest versions of product safety information sheets (PSIS), product safety data sheets (SDS) and other product liability documents are available in our website [www.borealisgroup.com](http://www.borealisgroup.com).

### Sustainability aspects

Borealis is ever mindful of the impact of our products on the planet. We promote Design for Circularity (DfC) and Design for Recycling (DfR) to conserve natural resources and to reduce the environmental impact of products over their entire lifetime (including production, use phase and after phase). DfR helps ensure that material can be effectively recycled while maximizing the material performance efficiency.

Further information on sustainability and Design for Recycling (DfR) can be found from our websites [www.borealisgroup.com](http://www.borealisgroup.com) and [www.borealiseverminds.com](http://www.borealiseverminds.com).

### Disclaimer

Recycled plastics are subject to material inconsistencies. mtm/Exoplast makes no warranties which extend beyond the description contained herein and to the best of our knowledge, the information is accurate and reliable as of the date of publication. Because of the multitude of possible influences during the use and application of our products, the information included does not release customers and users from the obligation to examine and test them carefully. Please note that nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose as mtm/Exoplast do not know the origin of the product. Where necessary, the customer is recommended to obtain a feedstock release from the customer. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of any mtm/Exoplast product in conjunction with any other products and/or materials. The information contained herein relates exclusively to our products when not used in conjunction with any other material unless as specifically provided for in the test methods stated above. The product(s) mentioned herein are not intended to be used for food contact, drinking water contact, medical, pharmaceutical or healthcare applications and we do not support their use for such applications. Otherwise, our General Terms and Conditions of Sale apply.