

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Pyrolysis Gasoline

REACH Registration Number : 01-2119489289-18-0002, 01-2119489289-18-XXXX

Substance name : naphtha (petroleum), light steam-cracked

EC-No. : 265-187-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Manufacture, Use as an intermediate, Formulation

1.3 Details of the supplier of the safety data sheet

Manufacturer : Borealis Polymers Oy
P.O.Box 330, FI-06101 Porvoo, Finland
Telephone: +358 9 394900

Borealis AB
S-444 86 Stenungsund, Sweden
Telephone: +46 303 86000

Supplier : Borealis AG
Trabrennstrasse 6-8, 1020 Vienna, Austria
Telephone: +43 1 22400 0

E-mail address : sds@borealisgroup.com

1.4 Emergency telephone number

+1 760 476 3962 (3E), Access code: 336296

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.
Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Eye irritation, Category 2
Germ cell mutagenicity, Category 1B
Carcinogenicity, Category 1A
Reproductive toxicity, Category 2

Specific target organ toxicity - single exposure, Category 3, Central nervous system

Specific target organ toxicity - repeated exposure, Category 1
Aspiration hazard, Category 1

Long-term (chronic) aquatic hazard, Category 2

H319: Causes serious eye irritation.
H340: May cause genetic defects.
H350: May cause cancer.
H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.
H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure.
H304: May be fatal if swallowed and enters airways.

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Additional Labelling

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

The product is a complex combination of hydrocarbons obtained by the distillation of the products from a steam cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (-4°F to 374°F). This stream is likely to contain 10 vol. % or more benzene.

3.1 Substances

Substance name : naphtha (petroleum), light steam-cracked

EC-No. : 265-187-5

Chemical nature : Petroleum distillates

Components

Chemical name	CAS-No. EC-No.	Concentration (%) w/w)	M-Factor, SCL, ATE
Substance of unknown or variable composition, complex reaction products or biological material (UVCB) :			
Naphtha (petroleum), light steam-cracked; Low boiling point naphtha -unspecified	64742-83-2 265-187-5	<= 100	
Contains :			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

benzene	71-43-2 200-753-7	$\geq 25 - < 50$	
toluene	108-88-3 203-625-9	$\geq 5 - < 20$	
n-hexane	110-54-3 203-777-6	$\geq 1 - < 10$	specific concentration limit STOT RE 2; H373 $\geq 5 \%$
naphthalene	91-20-3 202-049-5	$\geq 0 - < 5$	

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Where there is potential for exposure:
Restrict access to authorised persons.
Provide specific activity training to operators to minimise exposures.
First aider needs to protect himself.
Wear respiratory protection.
Do not leave the victim unattended.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- If inhaled : Move to fresh air.
Do not leave the victim unattended.
Keep patient warm and at rest.
Immediate medical attention is required.
If breathing is difficult, give oxygen.
No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus.
If unconscious place in recovery position.
- In case of skin contact : Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothes and shoes.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Remove contact lenses.
In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

least 15 minutes.
Protect unharmed eye.
If symptoms persist, call a physician.
If eye irritation persists, consult a specialist.

If swallowed

: Do NOT induce vomiting.
If a person vomits when lying on his back, place him in the recovery position.
Immediate medical attention is required.
Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

: Eye contact:
Redness
Dilatation of the pupil

Skin contact:
Redness
Swelling of tissue

Inhalation:
Headache
Nausea
Cough
Breathing difficulties
discomfort in the chest
Shortness of breath

Risks

: May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility. Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: In case of ingestion, the stomach should be emptied by gastric lavage under qualified medical supervision.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder
Carbon dioxide (CO₂)
Foam
Water mist

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Vapours are heavier than air and may spread along floors.
Flash back possible over considerable distance.
Fire will produce dense black smoke containing hazardous combustion products (see section 10).
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

Further information : Keep people away from and upwind of spill/leak.
Observe the risk of explosion.
Remove all sources of ignition.
Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.
Avoid inhalation of vapour or mist.
Ensure adequate ventilation, especially in confined areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Remove all sources of ignition.

6.2 Environmental precautions

Prevent product from entering environment and drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

6.3 Methods and material for containment and cleaning up

Small amounts:

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Large amounts:

Dam up.

Remove from surface water (e.g. by skimming or siphoning).

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|---|---|--|
| Advice on safe handling | : | The following actions are recommended: Closed systems for handling, process and storage.
To be handled by trained personnel only.
Ensure adequate ventilation.
Container may be opened only under exhaust ventilation hood.
Avoid splashes.
Do not use compressed air for filling, discharging or handling.
Dispose of rinse water in accordance with local and national regulations.
Avoid inhalation of vapour or mist.
Ensure that eyewash stations and safety showers are close to the workstation location. |
| Advice on protection against fire and explosion | : | Keep product and empty container away from heat and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. |
| Hygiene measures | : | Ensure adequate ventilation. Avoid and prevent all spillage, contact and exposure. Smoking, eating and drinking should be prohibited in the application area. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|--|
| Requirements for storage areas and containers | : | Keep locked up or in an area accessible only to qualified or authorised persons. Keep container tightly closed and in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers. |
| Further information on | : | Vapours may form explosive mixtures with air. Keep away |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

storage conditions from sources of ignition - No smoking. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Advice on common storage : Keep away from incompatible materials.
See chapter 10.
Keep away from food, drink and animal feedingstuffs.

Packaging material : Suitable material: Mild steel, Stainless steel

7.3 Specific end use(s)

Specific use(s) : Reserved for industrial and professional use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
benzene	71-43-2	TWA	0,5 ppm 1,65 mg/m ³	2004/37/EC
Further information	Skin, Carcinogens or mutagens			
toluene	108-88-3	TWA	50 ppm 192 mg/m ³	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m ³	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m ³	2006/15/EC
Further information	Indicative			
naphthalene	91-20-3	TWA	10 ppm 50 mg/m ³	91/322/EEC
Further information	Indicative			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Pyrolysis Gasoline	Workers	Inhalation	Long-term systemic effects	3,25 mg/m ³
		Dermal	Long-term systemic effects	23,4 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,25 µg/m ³
		Oral	Long-term systemic effects	0,464 µg/kg/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Pyrolysis Gasoline		
Remarks:	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

8.2 Exposure controls

Engineering measures

Minimise exposure using measures such as closed systems, dedicated facilities and suitable general / local exhaust ventilation.

Ensure safe systems of work or equivalent arrangements are in place to manage risks.

Regularly inspect, test and maintain all control measures.

Personal protective equipment

Eye protection : Wear goggles and if needed face-shield.

Hand protection

Material : Viton

Break through time : > 240 min

Material : Neoprene

Break through time : > 10 min

Material : thick PVC

Remarks : Wear suitable gloves:
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. or

Skin and body protection : Wear suitable protective clothing and rubber boots.

Respiratory protection : In case of insufficient ventilation: Respirator with A2 or ABEK filter or self-contained breathing apparatus.

Protective measures : Provide specific activity training to operators to minimise exposures.

Consider the need for risk based health surveillance.

Environmental exposure controls

General advice : Prevent product from entering environment and drains.
Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : colourless, yellow, dark brown
Odour : aromatic
Odour Threshold : No data available

Melting point : < -25 °C

Boiling range : > 35 - 200 °C
Flammability : Highly flammable.

Upper explosion limit / Upper flammability limit : 8,0 %(V)
Benzene

Lower explosion limit / Lower flammability limit : 1,2 %(V)
Benzene

Flash point : < -10 °C

pH : No data available

Viscosity
Viscosity, kinematic : 0,6 - 1,5 mm²/s (20 °C)
0,47 - 0,71 mm²/s (40 °C)

Solubility(ies)
Water solubility : 0,035 - 0,16 g/l
Solubility in other solvents : No data available

Vapour pressure : 100 hPa (20 °C)
Benzene

Relative density : ca. 0,82

Relative vapour density : 2,7
Benzene

9.2 Other information

Self-ignition : > 400 °C
101,3 kPa

Surface tension : 70,2 - 72 mN/m

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Molecular weight : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Observe the risk of explosion.
Keep away from heat and sources of ignition.

10.5 Incompatible materials

Materials to avoid : Reacts violently with:
Oxidizing agents
Nitric acid
sulphuric acid
Fluorine
Chlorine
Bromine
May attack many plastics, rubbers and coatings.

10.6 Hazardous decomposition products

Under fire conditions:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Read-across (Analogy)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Acute inhalation toxicity : LD50 (Rat): mg/m³ 20000
Test substance: Read-across (Analogy)
Remarks: No adverse effect has been observed in acute toxicity tests.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Remarks: Read-across (Analogy)

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Result : Irritating to skin.
Test substance : Read-across (Analogy)

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit
Result : Irritating to eyes.
Test substance : Read-across (Analogy)

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Exposure routes : Dermal
Species : Guinea pig
Result : Does not cause skin sensitisation.
Test substance : Read-across (Analogy)

Germ cell mutagenicity

May cause genetic defects.

Product:

Genotoxicity in vivo : Method: OECD Test Guideline 475
Result: positive
Remarks: Read-across (Analogy)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Components:

benzene:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation
Result: positive

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: inhalation (vapour)
Method: OECD Test Guideline 474
Result: positive

Species: Human
Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

May cause cancer.

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

Components:

benzene:

Species : Rat, male and female
Application Route : Oral
Exposure time : 103 wks
Dose : 25 mg/kg bw/d
Frequency of Treatment : 1/d, 5 d/wk
Method : OECD Test Guideline 453

Species : Mouse, male and female
Application Route : Inhalation
Exposure time : 2 - 16 wks
Dose : 960 mg/m3
Frequency of Treatment : 6 h/d, 5 d/wk

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

Harmful: may cause lung damage if swallowed.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Neurological effects

Product:

Components of the product may affect the nervous system.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 13,3 mg/l Test Type: semi-static test Method: QSAR
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 23,3 mg/l Method: QSAR
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 9,82 mg/l End point: Growth rate Method: QSAR
Toxicity to fish (Chronic toxicity)	: EL10: 2,56 mg/l Method: QSAR
Toxicity to daphnia and other	: EL10: 4,44 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

aquatic invertebrates
(Chronic toxicity)

Species: Daphnia magna (Water flea)
Method: QSAR

Components:

benzene:

Toxicity to fish (Chronic toxicity)

: LOEC: 1,6 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Test Type: flow-through test

Toxicity to daphnia and other
aquatic invertebrates
(Chronic toxicity)

: NOEC: 3 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Test Type: semi-static test

12.2 Persistence and degradability

Product:

Biodegradability

: Result: Inherently biodegradable.
Method: QSAR

Components:

benzene:

Biodegradability

: Test Type: activated sludge
Result: Readily biodegradable.
Kinetic:
10 d: 88 %
28 d: 96 %
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Product:

Bioaccumulation

: Remarks: Bioaccumulation is unlikely.
Information given is based on data on the components and the ecotoxicology of similar products.

Components:

benzene:

Bioaccumulation

: Bioconcentration factor (BCF): 13
Method: QSAR
Remarks: Bioaccumulation not expected.
log Pow: 2,13

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

12.4 Mobility in soil

Product:

Distribution among environmental compartments : Adsorption/Soil
log Koc: 1,33 - 6,25
Method: QSAR
Remarks: Not expected to adsorb on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of as hazardous waste in compliance with local and national regulations.
European waste code:
07 01 04* (other organic solvents, washing liquids and mother liquors)
Where possible recycling is preferred to disposal or incineration.

Contaminated packaging : Handle with care.
Dispose of as hazardous waste in compliance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3295
IMDG : UN 3295
IATA (Cargo) : UN 3295

14.2 UN proper shipping name

ADR : HYDROCARBONS, LIQUID, N.O.S.
(benzene, toluene)
IMDG : HYDROCARBONS, LIQUID, N.O.S.
(benzene, toluene)
IATA (Cargo) : Hydrocarbons, liquid, n.o.s.
(benzene, toluene)

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA (Cargo) : 3

14.4 Packing group

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)
IMDG
Packing group : II
Labels : 3
EmS Code : F-E, S-D
IATA (Cargo)
Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Ship type : 2
Pollution category : Y
Remarks : Product name in English: BENZENE AND MIXTURES
HAVING 10% BENZENE OR MORE (I)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3
Naphtha (petroleum), light steam-cracked; Low boiling point naphtha - unspecified (Number on list 29, 28)
benzene (Number on list 72, 5, 29, 28)
toluene (Number on list 48)
n-hexane
2-methylpentane
naphthalene
2,2-dimethylbutane

benzene (Number on list 72, 5, 29, 28)
toluene (Number on list 48)
Naphtha (petroleum), light steam-cracked; Low boiling point naphtha - unspecified (Number on list 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Category P5c	FLAMMABLE LIQUIDS	Quantity 1 5.000 t	Quantity 2 50.000 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of other abbreviations

2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
2006/15/EC	:	Europe. Indicative occupational exposure limit values
91/322/EEC	:	Europe. Commission Directive 91/322/EEC on establishing indicative limit values
2004/37/EC / TWA	:	Long term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
91/322/EEC / TWA	:	Limit Value - eight hours

Further information

Other information	:	Changes since the last version are highlighted in the margin.
-------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

This version replaces all previous versions.
The classification corresponds to the current EC listing, but is enhanced by specialised literature data and the Company's own information.

Issuer : Borealis, Group Product Stewardship

Sources of key data used to compile the Safety Data Sheet : Chemical Safety Report, Naphtha (petroleum), light steam-cracked. Lower Olefins and Aromatics REACH Consortium, 2024
International Chemical Safety Card, Benzene
(<http://www.inchem.org/documents/icsc/icsc/eics0015.htm>)

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Muta. 1B	H340
Carc. 1A	H350
Repr. 2	H361fd
STOT SE 3	H336
STOT RE 1	H372
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Annex: Exposure Scenarios

Table of Contents

Number	Title
ES1	Manufacture, Manufacture of substance
ES2	Formulation or re-packing, Formulation & (re)packing of substances and mixtures
ES3	Use at industrial sites, Use as an intermediate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

ES1: Manufacture of substance

1.1. Title section

Structured Short Title	: Manufacture, Manufacture of substance
-------------------------------	---

Environment		
CS1	Environment	ERC1
Worker		
CS2	General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, PROC28
CS3	General exposures (closed systems)	PROC1
CS4	General exposures (closed systems), With sample collection	PROC2
CS5	General exposures (closed systems), Batch process	PROC3
CS6	General exposures	PROC4
CS7	Process sampling	PROC9
CS8	Laboratory activities	PROC15
CS9	Bulk transfers, Closed systems	PROC8b
CS10	Bulk transfers	PROC8b
CS11	Bulk transfers	PROC8b
CS12	Equipment cleaning and maintenance	PROC8a, PROC28
CS13	Storage	PROC1
CS14	Storage	PROC2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Manufacture of the substance (ERC1)

Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 2167 tonnes/day
Emission days	: 300
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 10.000 m³/d
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

1.2.2. Control of worker exposure: General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used, frequency and duration of use (or from service life)	
Duration	: Covers daily exposures up to 8 hours (unless stated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

differently).
Conditions and measures related to personal protection, hygiene and health evaluation
General measures (eye irritants) Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply
General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

1.2.3. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

1.2.4. Control of worker exposure: General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Use in closed, continuous process with occasional controlled exposure	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes process temperature up to 20 °C

1.2.5. Control of worker exposure: General exposures (closed systems), Batch process Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Closed batch process with occasional controlled exposure	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

Temperature : Assumes process temperature up to 20 °C

1.2.6. Control of worker exposure: General exposures

Chemical production where opportunity for exposure arises (PROC4)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 1 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.2.7. Control of worker exposure: Process sampling

Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 0,25 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.2.8. Control of worker exposure: Laboratory activities

Use as laboratory reagent (PROC15)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation
Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.2.9. Control of worker exposure: Bulk transfers, Closed systems

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Ensure material transfers are under containment or extract ventilation.

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.2.10. Control of worker exposure: Bulk transfers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Ensure material transfers are under containment or extract ventilation.

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

1.2.11. Control of worker exposure: Bulk transfers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Wear suitable respiratory protection. Efficiency: APF 10	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Outdoor use
Temperature	: Assumes process temperature up to 20 °C

1.2.12. Control of worker exposure: Equipment cleaning and maintenance

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) /

Manual maintenance (cleaning and repair) of machinery (PROC28)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Drain down and flush system prior to equipment break-in or maintenance. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Wear suitable respiratory protection.

Efficiency: APF 10

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.2.13. Control of worker exposure: Storage

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

1.2.14. Control of worker exposure: Storage

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Store substance within a closed system.

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Manufacture of the substance (ERC1)

Compartment	Exposure level	RCR
Freshwater	0,281 mg/L	0,848
Marine water	0,028 mg/L	0,085
Freshwater sediment	1,72 µg/kg dry weight	0,97
Marine sediment	0,172 mg/kg dry weight	0,097
Agricultural soil	0,169 mg/kg dry weight	0,327

1.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,00099 mg/cm²		Benzene
dermal	local	short-term	0,00099 mg/cm²		Benzene
combined routes	systemic	long-term		0,012	

1.3.4. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m ³	0,61	Benzene
inhalative	systemic	short-term	1,953 mg/m ³		Benzene
dermal	systemic	long-term	0,137 mg/kg bw/day	0,274	Benzene
dermal	local	long-term	0,02 mg/cm ²		Benzene
dermal	local	short-term	0,02 mg/cm ²		Benzene
combined routes	systemic	long-term		0,274	

1.3.5. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,041 mg/kg bw/day	0,138	Benzene
dermal	local	long-term	0,012 mg/cm ²		Benzene
dermal	local	short-term	0,012 mg/cm ²		Benzene
combined routes	systemic	long-term		0,138	

1.3.6. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,391 mg/m ³	0,488	Benzene
inhalative	systemic	short-term	7,811 mg/m ³		Benzene
dermal	systemic	long-term	0,069 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,01 mg/cm ²		Benzene
dermal	local	short-term	0,01 mg/cm ²		Benzene
combined routes	systemic	long-term		0,686	

1.3.7. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m ³	0,61	Benzene
inhalative	systemic	short-term	19,52 mg/m ³		Benzene
dermal	systemic	long-term	0,034 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,0001 mg/cm ²		Benzene
dermal	local	short-term	0,0001 mg/cm ²		Benzene
combined routes	systemic	long-term		0,686	

1.3.8. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,02 mg/kg bw/day	0,068	Benzene
dermal	local	long-term	0,0060 mg/cm ²		Benzene
dermal	local	short-term	0,0060 mg/cm ²		Benzene
combined routes	systemic	long-term		0,068	

1.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,069	

1.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure	Exposure level	RCR	Remarks
----------------	---------------	----------	----------------	-----	---------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

		indicator			
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,069	

1.3.11. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,171 mg/m ³	0,214	Benzene
inhalative	systemic	short-term	1,139 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,069	

1.3.12. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,293 mg/m ³	0,366	Benzene
inhalative	systemic	short-term	1,953 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,137	

1.3.13. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m ³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m ³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,0010 mg/cm ²		Benzene
dermal	local	short-term	0,0010 mg/cm ²		Benzene
combined routes	systemic	long-term		< 0,01	

1.3.14. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,082 mg/kg bw/day	0,274	Benzene
dermal	local	long-term	0,012 mg/cm ²		Benzene
dermal	local	short-term	0,012 mg/cm ²		Benzene
combined routes	systemic	long-term		0,274	

Additional information on exposure estimation

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not enable the derivation of a DNEL for eye irritant effects.
Risk management measures are based on qualitative risk characterisation.
Predicted exposures are not expected to exceed the DN(M)EL when the risk management measures/operational conditions outlined in section 2 are implemented.

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

ES2: Formulation & (re)packing of substances and mixtures

2.1. Title section

Structured Short Title	: Formulation or re-packing, Formulation & (re)packing of substances and mixtures
-------------------------------	---

Environment

CS1	Formulation & (re)packing of substances and mixtures	ERC2
------------	---	-------------

Worker

CS2	General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, PROC28
------------	---	---

CS3	General exposures (closed systems)	PROC1
------------	---	--------------

CS4	General exposures (closed systems), With sample collection	PROC2
------------	---	--------------

CS5	General exposures (closed systems), Batch process	PROC3
------------	--	--------------

CS6	General exposures	PROC4
------------	--------------------------	--------------

CS7	Batch processes at elevated temperatures, Use in contained batch processes	PROC3
------------	---	--------------

CS8	Process sampling	PROC9
------------	-------------------------	--------------

CS9	Laboratory activities	PROC15
------------	------------------------------	---------------

CS10	Bulk transfers, Dedicated facility	PROC8b
-------------	---	---------------

CS11	Mixing operations (open systems)	PROC5
-------------	---	--------------

CS12	Manual, Transfer from/pouring from containers, Non-dedicated facility	PROC8a
-------------	--	---------------

CS13	Drum/batch transfers, Dedicated facility	PROC8b
-------------	---	---------------

CS14	Tabletting, compression, extrusion or pelletisation	PROC14
-------------	--	---------------

CS15	Drum and small package filling	PROC9
-------------	---------------------------------------	--------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

CS16	Equipment cleaning and maintenance	PROC8a, PROC28
CS17	Storage	PROC1
CS18	Storage	PROC2

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 2167 tonnes/day
Emission days	: 300
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

2.2.2. Control of worker exposure: General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15) / Manual maintenance (cleaning and repair) of machinery (PROC28)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used, frequency and duration of use (or from service life)	
Duration	: Covers daily exposures up to 8 hours (unless stated differently).
Conditions and measures related to personal protection, hygiene and health evaluation	
General measures (eye irritants) Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	
General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.	

2.2.3. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures
Occupational Health and Safety Management System: Advanced
Closed systems
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.4. Control of worker exposure: General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced
Use in closed, continuous process with occasional controlled exposure

Local exhaust ventilation
Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

Temperature : Assumes process temperature up to 20 °C

2.2.5. Control of worker exposure: General exposures (closed systems), Batch process Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Closed batch process with occasional controlled exposure	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes process temperature up to 20 °C

2.2.6. Control of worker exposure: General exposures

Chemical production where opportunity for exposure arises (PROC4)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 1 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

2.2.7. Control of worker exposure: Batch processes at elevated temperatures, Use in contained batch processes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 0,25 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Closed batch process with occasional controlled exposure	
Local exhaust ventilation Formulate in enclosed or ventilated mixing vessels. Ensure material transfers are under containment or extract ventilation. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 60 °C

2.2.8. Control of worker exposure: Process sampling

Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 0,25 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.9. Control of worker exposure: Laboratory activities

Use as laboratory reagent (PROC15)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation
Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.10. Control of worker exposure: Bulk transfers, Dedicated facility

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Ensure material transfers are under containment or extract ventilation.

Inhalation - minimum efficiency of 95 %

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.11. Control of worker exposure: Mixing operations (open systems)

Mixing or blending in batch processes (PROC5)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Local exhaust ventilation

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of 95 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Respiratory protection

Efficiency: APF 10

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.12. Control of worker exposure: Manual, Transfer from/pouring from containers, Non-dedicated facility

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 95 %	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Respiratory protection Efficiency: APF 10	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

2.2.13. Control of worker exposure: Drum/batch transfers, Dedicated facility Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

2.2.14. Control of worker exposure: Tableting, compression, extrusion or pelletisation Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Handle substance within a predominantly closed system provided with extract ventilation. Inhalation - minimum efficiency of 95 %	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Respiratory protection Efficiency: APF 10	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

2.2.15. Control of worker exposure: Drum and small package filling Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

Fill containers/cans at dedicated fill points supplied with local extract ventilation.

Inhalation - minimum efficiency of 95 %

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Respiratory protection

Efficiency: APF 10

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.2.16. Control of worker exposure: Equipment cleaning and maintenance

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) /

Manual maintenance (cleaning and repair) of machinery (PROC28)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

Drain down and flush system prior to equipment break-in or maintenance.

Inhalation - minimum efficiency of 95 %

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Respiratory protection

Efficiency: APF 10

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Temperature	:	Assumes process temperature up to 20 °C
-------------	---	---

2.2.17. Control of worker exposure: Storage

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Store substance within a closed system.		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %		
Other conditions affecting workers exposure		
Indoor or outdoor use	:	Outdoor use
Temperature	:	Assumes process temperature up to 20 °C

2.2.18. Control of worker exposure: Storage

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)		
Duration	:	Covers use up to 4 h
Technical and organisational conditions and measures		
Occupational Health and Safety Management System: Advanced		
Use in closed, continuous process with occasional controlled exposure Store substance within a closed system.		
Local exhaust ventilation Inhalation - minimum efficiency of 95 %		
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Compartment	Exposure level	RCR
Freshwater	0,271 mg/L	0,792
Marine water	0,0271 mg/L	0,079
Freshwater sediment	1,61 µg/kg dry weight	0,907
Marine sediment	0,161 µg/kg dry weight	0,091
Agricultural soil	0,0836 µg/kg dry weight	0,162

2.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,00099 mg/cm²		Benzene
dermal	local	short-term	0,00099 mg/cm²		Benzene
combined routes	systemic	long-term		< 0,01	

2.3.4. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m³	0,61	Benzene
inhalative	systemic	short-term	1,953 mg/m³		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	systemic	long-term	0,137 mg/kg bw/day	0,274	Benzene
dermal	local	long-term	0,02 mg/cm2		Benzene
dermal	local	short-term	0,02 mg/cm2		Benzene
combined routes	systemic	long-term		0,274	

2.3.5. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,041 mg/kg bw/day	0,138	Benzene
dermal	local	long-term	0,012 mg/cm2		Benzene
dermal	local	short-term	0,012 mg/cm2		Benzene
combined routes	systemic	long-term		0,138	

2.3.6. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,391 mg/m ³	0,488	Benzene
inhalative	systemic	short-term	7,811 mg/m ³		Benzene
dermal	systemic	long-term	0,069 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,01 mg/cm2		Benzene
dermal	local	short-term	0,01 mg/cm2		Benzene
combined routes	systemic	long-term		0,686	

2.3.7. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m ³	0,61	Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

inhalative	systemic	short-term	19,52 mg/m ³		Benzene
dermal	systemic	long-term	0,0035 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,001 mg/cm ²		Benzene
dermal	local	short-term	0,001 mg/cm ²		Benzene
combined routes	systemic	long-term		< 0,01	

2.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m ³	0,61	Benzene
inhalative	systemic	short-term	19,52 mg/m ³		Benzene
dermal	systemic	long-term	0,034 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,005 mg/cm ²		Benzene
dermal	local	short-term	0,005 mg/cm ²		Benzene
combined routes	systemic	long-term		0,686	

2.3.9. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,01 mg/kg bw/day	0,034	Benzene
dermal	local	long-term	0,0030 mg/cm ²		Benzene
dermal	local	short-term	0,0030 mg/cm ²		Benzene
combined routes	systemic	long-term		0,034	

2.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,069	

2.3.11. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,06 mg/cm2		Benzene
dermal	local	short-term	0,06 mg/cm2		Benzene
combined routes	systemic	long-term		0,137	

2.3.12. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,137	

2.3.13. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,069	

2.3.14. Worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,206 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,686	

2.3.15. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,206 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,686	

2.3.16. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	systemic	long-term	0,411 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,137	

2.3.17. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m ³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m ³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,00099 mg/cm ²		Benzene
dermal	local	short-term	0,00099 mg/cm ²		Benzene
combined routes	systemic	long-term		< 0,01	

2.3.18. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,041 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,0060 mg/cm ²		Benzene
dermal	local	short-term	0,006 mg/cm ²		Benzene
combined routes	systemic	long-term		0,137	

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

ES3: Use as an intermediate

3.1. Title section

Structured Short Title	: Use at industrial sites, Use as an intermediate
-------------------------------	---

Environment		
CS1	Environment	ERC6a
Worker		
CS2	General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, PROC28
CS3	General exposures (closed systems)	PROC1
CS4	General exposures (closed systems), With sample collection	PROC2
CS5	General exposures (closed systems), Batch process	PROC3
CS6	General exposures (open systems)	PROC4
CS7	Process sampling	PROC9
CS8	Laboratory activities	PROC15
CS9	Bulk transfers, Closed systems	PROC8b
CS10	Bulk transfers	PROC8b
CS11	Bulk transfers	PROC8b
CS12	Equipment cleaning and maintenance	PROC8a, PROC28
CS13	Storage	PROC1
CS14	Storage	PROC2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Use of intermediate (ERC6a)

Amount used, frequency and duration of use (or from service life)	
Daily amount per site	: 2167 tonnes/day
Emission days	: 300
Conditions and measures related to sewage treatment plant	
STP type	: Onsite Sewage Treatment Plant
STP effluent	: 2.000 m³/d
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

3.2.2. Control of worker exposure: General measures (eye irritants), General measures (skin irritants), General measures (carcinogens), General risk management measures applicable to all activities

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) / Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used, frequency and duration of use (or from service life)	
Duration	: Covers daily exposures up to 8 hours (unless stated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

differently).
Conditions and measures related to personal protection, hygiene and health evaluation
General measures (eye irritants) Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General measures (skin irritants) Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply
General measures (carcinogens) Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

3.2.3. Control of worker exposure: General exposures (closed systems)

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Use in closed process	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

3.2.4. Control of worker exposure: General exposures (closed systems), With sample collection Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Use in closed, continuous process with occasional controlled exposure	
Local exhaust ventilation	
Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.2.5. Control of worker exposure: General exposures (closed systems), Batch process Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Closed batch process with occasional controlled exposure	
Local exhaust ventilation	
Handle substance within a predominantly closed system provided with extract ventilation.	
Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor

Temperature : Assumes process temperature up to 20 °C

3.2.6. Control of worker exposure: General exposures (open systems)

Chemical production where opportunity for exposure arises (PROC4)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Local exhaust ventilation

Inhalation - minimum efficiency of 95 %

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

3.2.7. Control of worker exposure: Process sampling

Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 1 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Wear suitable respiratory protection. Efficiency: APF 10	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.2.8. Control of worker exposure: Laboratory activities Use as laboratory reagent (PROC15)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.2.9. Control of worker exposure: Bulk transfers, Closed systems Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Ensure material transfers are under containment or extract ventilation. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.2.10. Control of worker exposure: Bulk transfers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Ensure material transfers are under containment or extract ventilation. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

3.2.11. Control of worker exposure: Bulk transfers

Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Wear suitable respiratory protection. Efficiency: APF 10	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.2.12. Control of worker exposure: Equipment cleaning and maintenance

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) /

Manual maintenance (cleaning and repair) of machinery (PROC28)

Amount used, frequency and duration of use (or from service life)	
Duration	: Covers use up to 4 h
Technical and organisational conditions and measures	
Occupational Health and Safety Management System: Advanced	
Local exhaust ventilation Drain down and flush system prior to equipment break-in or maintenance. Inhalation - minimum efficiency of 95 %	
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Dermal - minimum efficiency of 95 %

Wear suitable respiratory protection.

Efficiency: APF 10

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Temperature : Assumes process temperature up to 20 °C

3.2.13. Control of worker exposure: Storage

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Dermal - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Outdoor use

Temperature : Assumes process temperature up to 20 °C

3.2.14. Control of worker exposure: Storage

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Amount used, frequency and duration of use (or from service life)

Duration : Covers use up to 4 h

Technical and organisational conditions and measures

Occupational Health and Safety Management System: Advanced

Use in closed, continuous process with occasional controlled exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

Store substance within a closed system.	
Local exhaust ventilation Inhalation - minimum efficiency of 95 %	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Temperature	: Assumes process temperature up to 20 °C

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Use of intermediate (ERC6a)

Compartment	Exposure level	RCR
Freshwater	0,271 mg/L	0,793
Marine water	0,0271 mg/L	0,079
Freshwater sediment	1,61 µg/kg dry weight	0,907
Marine sediment	0,161 µg/kg dry weight	0,091
Agricultural soil	0,0348 µg/kg dry weight	0,065

3.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m ³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m ³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,00099 mg/cm ²		Benzene
dermal	local	short-term	0,00099 mg/cm ²		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

combined routes	systemic	long-term		< 0,01	
-----------------	----------	-----------	--	--------	--

3.3.4. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,488 mg/m ³	0,61	Benzene
inhalative	systemic	short-term	1,953 mg/m ³		Benzene
dermal	systemic	long-term	0,137 mg/kg bw/day	0,274	Benzene
dermal	local	long-term	0,02 mg/cm ²		Benzene
dermal	local	short-term	0,02 mg/cm ²		Benzene
combined routes	systemic	long-term		0,274	

3.3.5. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,041 mg/kg bw/day	0,138	Benzene
dermal	local	long-term	0,012 mg/cm ²		Benzene
dermal	local	short-term	0,012 mg/cm ²		Benzene
combined routes	systemic	long-term		0,138	

3.3.6. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,273 mg/m ³	0,342	Benzene
inhalative	systemic	short-term	1,823 mg/m ³		Benzene
dermal	systemic	long-term	0,206 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	local	short-term	0,03 mg/cm2		Benzene
combined routes	systemic	long-term		0,686	

3.3.7. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,228 mg/m ³	0,285	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,069 mg/kg bw/day	0,686	Benzene
dermal	local	long-term	0,01 mg/cm2		Benzene
dermal	local	short-term	0,01 mg/cm2		Benzene
combined routes	systemic	long-term		0,686	

3.3.8. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,586 mg/m ³	0,732	Benzene
inhalative	systemic	short-term	3,906 mg/m ³		Benzene
dermal	systemic	long-term	0,02 mg/kg bw/day	0,068	Benzene
dermal	local	long-term	0,0060 mg/cm2		Benzene
dermal	local	short-term	0,0060 mg/cm2		Benzene
combined routes	systemic	long-term		0,068	

3.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm2		Benzene
dermal	local	short-term	0,03 mg/cm2		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

combined routes	systemic	long-term		0,069	
-----------------	----------	-----------	--	-------	--

3.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,732 mg/m ³	0,915	Benzene
inhalative	systemic	short-term	4,882 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,069	

3.3.11. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,171 mg/m ³	0,214	Benzene
inhalative	systemic	short-term	1,139 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,069	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene
dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,069	

3.3.12. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Manual maintenance (cleaning and repair) of machinery (PROC28)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,293 mg/m ³	0,366	Benzene
inhalative	systemic	short-term	1,953 mg/m ³		Benzene
dermal	systemic	long-term	0,411 mg/kg bw/day	0,137	Benzene
dermal	local	long-term	0,03 mg/cm ²		Benzene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Pyrolysis Gasoline

Version 14.0

Revision Date: 07.04.2025

Former date: 25.04.2024

dermal	local	short-term	0,03 mg/cm ²		Benzene
combined routes	systemic	long-term		0,137	

3.3.13. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,023 mg/m ³	0,028	Benzene
inhalative	systemic	short-term	0,091 mg/m ³		Benzene
dermal	systemic	long-term	0,0034 mg/kg bw/day	< 0,01	Benzene
dermal	local	long-term	0,0010 mg/cm ²		Benzene
dermal	local	short-term	0,0010 mg/cm ²		Benzene
combined routes	systemic	long-term		< 0,01	

3.3.14. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure level	RCR	Remarks
inhalative	systemic	long-term	0,683 mg/m ³	0,854	Benzene
inhalative	systemic	short-term	4,557 mg/m ³		Benzene
dermal	systemic	long-term	0,082 mg/kg bw/day	0,274	Benzene
dermal	local	long-term	0,012 mg/cm ²		Benzene
dermal	local	short-term	0,012 mg/cm ²		Benzene
combined routes	systemic	long-term		0,274	

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.