

SAFETY DATA SHEET

Visico™ LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

SECTION 1. IDENTIFICATION

Product name : Visico LE4433

Manufacturer or supplier's details

Supplier : Borealis Compounds Inc
176 Thomas Road, NJ 07865 Port Murray, United States of America (USA)
Telephone: +1 908 850 6200

E-mail address : sds@borealisgroup.com

Emergency telephone number : +1 866 519 4752 (3E) Access code: 336296Borealis Compounds Inc, Borealis North America HSE: 908-850-6200 for Monday – Friday 8-4:30pm excluding holidays

Recommended use of the chemical and restrictions on use

Recommended use : Raw material for plastics industry
Restrictions on use : Use only according to our recommendations.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity : Category 1B

Specific target organ toxicity - repeated exposure : Category 1 (Immune system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H360D May damage the unborn child.
H372 Causes damage to organs (Immune system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Visico is a trademark of the Borealis group.

Borealis AG | Trabrennstrasse 6-8 | 1020 Vienna | Austria
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333
FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Warning!

May form combustible dust concentrations in air (during processing).

The product burns, but is not classified as flammable.

During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released.

In contact with water or moisture methanol will be released.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : The product is a polyethylene copolymer.
It contains carbon black.
It contains stabilisers.

Components

Chemical name	CAS-No.	Concentration (% w/w)
carbon black	1333-86-4	$\geq 30 - < 50$
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	68610-51-5	$\geq 1 - < 2.5$
dioctyltin dilaurate	3648-18-8	$\geq 1 - < 2.5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of vapours or decomposition products.
Seek medical advice immediately.

In case of skin contact : If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage.
Obtain medical attention.
Wash off with soap and plenty of water.
Call a physician if irritation develops or persists.

In case of eye contact : Rinse thoroughly with plenty of water, also under the eyelids.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

- If swallowed : If swallowed, rinse mouth with water (only if the person is conscious).
Seek medical advice immediately.
- Most important symptoms and effects, both acute and delayed : Inhalation of dust may irritate the respiratory tract.
Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.
Symptoms of poisoning (methanol):
Daze
Dizziness
Nausea
Abdominal pain
Respiratory disorders
Symptoms of poisoning, prolonged exposure (methanol):
Blindness
May damage the unborn child.
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
No specific instructions needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water in spread jet, dry chemicals, foam or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Principal toxicant in the smoke is carbon monoxide.

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment.

Should not be released into the environment.
- Methods and materials for containment and cleaning up : Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Non-sparking tools should be used.
Vacuum or sweep up spill.
All spill of material must be removed immediately to prevent

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

slipping accidents.
Recycle or dispose loose material properly.
Do not flush into surface water or sanitary sewer system.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Dust from the product gives a potential risk for dust explosion. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. All equipment shall be grounded.
- Advice on safe handling : During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released. Provide adequate ventilation. Local exhaust ventilation may be necessary. Avoid inhalation of dust and decomposition fumes. Avoid contact with skin and eyes.
- Conditions for safe storage : Store locked up.
- Further information on storage stability : Keep in a dry place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
carbon black	1333-86-4	TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1
		TWA	3.5 mg/m ³	OSHA P0
		TWA	0.1 mg/m ³ (PAHs)	NIOSH REL
		TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
dioctyltin dilaurate	3648-18-8	TWA	0.1 mg/m ³ (Tin)	OSHA Z-1
		TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH
		TWA	0.1 mg/m ³ (Tin)	OSHA P0
		TWA	0.1 mg/m ³ (Tin)	NIOSH REL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		ST	250 ppm 325 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA Z-1
		TWA	200 ppm 260 mg/m ³	OSHA P0
		STEL	250 ppm 325 mg/m ³	OSHA P0

Engineering measures : Provide adequate ventilation.
Local exhaust ventilation may be necessary.

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment.

Personal protective equipment

Respiratory protection : In case of dust development use dust mask.
In the case of vapour formation use a respirator with an approved filter.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Material : Fluorinated rubber
Break through time : >= 480 min
Glove thickness : 0.4 mm

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

Eye protection : danger of cuts, abrasion, and the contact time.
Safety glasses
Skin and body protection : Protective clothing
Hygiene measures : When using do not eat, drink or smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pellets

Colour : black

Odour : odourless

Odour Threshold : Methanol: Do NOT rely on the odour: olfactory level is above the exposure limit.

pH : Not applicable insoluble

Melting range : 212 - 284 °F / 100 - 140 °C

Boiling range : Decomposes on heating.

Flash point : Not applicable (solid)

Evaporation rate : Not applicable (solid)

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapour pressure : Not applicable (solid)

Relative vapour density : Not applicable

Density : 1.1 - 1.2 g/cm³

Bulk density : 600 - 700 kg/m³

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable insoluble

Auto-ignition temperature : > 608 °F / > 320 °C

Viscosity
Viscosity, kinematic : No data available

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	3 - 10 mm Method: Image analysis (surface-based)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	The product is a stable thermoplastic, with no chemical reactivity. The intended crosslinking reaction occurs in combination with the base resin and moisture: at ambient conditions, in sauna or hot water bath.
Possibility of hazardous reactions	:	In contact with water or moisture methanol will be released.
Conditions to avoid	:	Exposure to moisture Extremes of temperature and direct sunlight.
Incompatible materials	:	None known.
Hazardous decomposition products	:	Under fire conditions: Carbon monoxide During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released. During crosslinking reaction in combination with base resin: methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

Carcinogenicity

Based on available data, the classification criteria are not met.

IARC Group 2B: Possibly carcinogenic to humans
carbon black 1333-86-4

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage the unborn child.

Components:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Effects on fertility : Test Type: Pre-/postnatal development
Species: Rabbit, female
Application Route: Oral
Dose: 50 mg/kg
Method: OECD Test Guideline 414
Result: Some evidence of adverse effects on development, based on animal experiments.
GLP: yes

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Causes damage to organs (Immune system) through prolonged or repeated exposure.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released. Methanol: Toxic by inhalation, in contact with skin and if swallowed. Causes damage to organs.

Remarks : Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No effect up to the limit of solubility.

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 0.2 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No effect up to the limit of solubility.

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (fresh water algae)): > 0.2
plants : mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No effect up to the limit of solubility.

Persistence and degradability**Product:**

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: Does not accumulate in organisms.

Mobility in soil**Product:**

Mobility : Remarks: Not expected to adsorb on soil.
Remarks: The product is insoluble and sinks in water.

Other adverse effects**Product:**

Additional ecological : Should not be released into the environment.
information

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : This substance, when discarded or disposed of is not specifically listed as a hazardous waste in Federal regulations. However, it could be hazardous if it is considered toxic, corrosive, ignitable or reactive according to Federal definitions (40 CFR 261). Additionally, it could be designated as hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact or mixing may have occurred, check 40 CFR 261 to determine whether it is a hazardous waste.
The transportation, storage, treatment and disposal of this waste material must be conducted in accordance with all applicable Federal, state and local regulations.
- Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Remarks : Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

SECTION 15. REGULATORY INFORMATION

California Prop. 65

|| This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

Safety, health and environmental regulations/legislation specific for the substance or mixture

Borealis certifies that all chemical substances in this shipment comply with all applicable rules or orders under TSCA and that Borealis is not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.


Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. The product is classified and labelled in accordance with Hazard Communication Standard 2012 (29 CFR 1910.1200)

US. Drug Enforcement Administration (DEA) Listed : Not applicable
Precursor and Essential Chemicals (21 CFR 1310)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Sources of key data used to : Safety data sheets of raw material suppliers.
compile the Safety Data
Sheet
Revision Date : 04/16/2024

SAFETY DATA SHEET

Visico LE4433

Version 6.0

Revision Date 04/16/2024

Former date 11/22/2021

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

US / EN