VisicoTM I E4439

Revision Date 04/25/2024	Former date 10/26/2023
: Visico LE4439	
s details	
: Borealis Compounds Inc 176 Thomas Road, NJ 07865 Por America (USA) Telephone: +1 908 850 6200	rt Murray, United States of
: <u>sds@borealisgroup.com</u>	
+1 866 519 4752 (3E) Access coo Compounds Inc, Borealis North A for Monday – Friday 8-4:30pm ex	merica HSE: 908-850-6200
	 Visico LE4439 s details Borealis Compounds Inc 176 Thomas Road, NJ 07865 Por America (USA) Telephone: +1 908 850 6200 sds@borealisgroup.com +1 866 519 4752 (3E) Access coo Compounds Inc, Borealis North A

ommended use of the chemical and restrictions on use

Recommended use	:	Raw material for plastics industry
Restrictions on use	:	Use only according to our recommendations.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accorda 1910.1200)	an	ce with the OSHA Hazard Communication Standard (29 CFR
Reproductive toxicity	:	Category 1B
Specific target organ toxicity - repeated exposure	:	Category 1 (Immune system)
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H360D May damage the unborn child. H372 Causes damage to organs (Immune system) through prolonged or repeated exposure.
Precautionary statements	:	Prevention:
		 P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

Visico is a trademark of the Borealis group.



ersion 6.0	Revision Date 04/25/2024	Former date 10/26/2023
6131011 0.0	Revision Date 04/25/2024	
	P280 Wear protective gloves/ prote face protection.	ective clothing/ eye protection/
	Response:	
	P308 + P313 IF exposed or concert attention.	rned: Get medical advice/
	Storage:	
	P405 Store locked up.	
	Disposal:	
	P501 Dispose of contents/ contain disposal plant.	er to an approved waste
Other hazards		
Warning!		
	ust concentrations in air (during processing).	
	s not classified as flammable. tion in combination with base resin: methanol	(Elam Lig 2: H225 Acute
	. 3; H311, Acute Tox. 3; H331, STOT SE 1; F	

Substance / Mixture	:	Mixture
Chemical nature	:	The product is a polyethylene copolymer.
		It contains stabilisers.

Components

Chemical name	CAS-No.	Concentration (% w/w)
dioctyltin dilaurate	3648-18-8	>= 1 - < 3
zinc dioctadecanoate	557-05-1	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Seek medical advice immediately.
In case of skin contact	:	If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage. Obtain medical attention. Wash off with soap and plenty of water. Call a physician if irritation develops or persists.
In case of eye contact	:	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately.
Most important symptoms and effects, both acute and	:	Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products



Borealis AG | Trabrennstrasse 6-8 | 1020 Vienna | Austria Telephone +43 1 224 00 0 | Fax +43 1 22 400 333 FN 269858a | CCC Commercial Court of Vienna | Website <u>www.borealisgroup.com</u>

Visico LE4439

firefighting

Version 6.0	Revision Date 04/25/2024	Former date 10/26/2023
delayed	may give headache or irritation of th Symptoms of poisoning (methanol) Daze Dizziness Nausea Abdominal pain Respiratory disorders Symptoms of poisoning, prolonged Blindness May damage the unborn child. Causes damage to organs through exposure.	exposure (methanol):
Notes to physician	: Treat symptomatically. No specific instructions needed.	
SECTION 5. FIREFIGHTING MEAS	SURES	
Suitable extinguishing media Unsuitable extinguishing media	Water in spread jet, dry chemicals,High volume water jet	foam or carbon dioxide.
Specific hazards during	: Principal toxicant in the smoke is ca	arbon monoxide.

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Special protective equipment : Wear self-contained breathing apparatus and protective suit. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation.
Environmental precautions	:	It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment. Should not be released into the environment.
Methods and materials for containment and cleaning up	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Non-sparking tools should be used. Vacuum or sweep up spill. All spill of material must be removed immediately to prevent slipping accidents. Recycle or dispose loose material properly. Do not flush into surface water or sanitary sewer system.



storage stability

Visico LE4439		
Version 6.0	Revision Date 04/25/2024	Former date 10/26/2023
SECTION 7. HANDLING AND STO	DRAGE	
Advice on protection against fire and explosion	: Dust from the product gives a pote Minimize dust generation and accu Routine housekeeping should be ir dusts do not accumulate on surfac All equipment shall be grounded.	Imulation. Instituted to ensure that
Advice on safe handling Conditions for safe storage Further information on	 During processing and thermal treat amounts of volatile hydrocarbons r Provide adequate ventilation. Local exhaust ventilation may be n Avoid inhalation of dust and decom Avoid contact with skin and eyes. Store locked up. Keep in a dry place. 	nay be released. ecessary.
	. Reep in a dry place.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dioctyltin dilaurate	3648-18-8	TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
zinc dioctadecanoate	557-05-1	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWÁ (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable	10 mg/m3	ACGIH



Vision | E4420

sion 6.0	Revision I	Date 04/25/2024	Form	er date 10/26/20
		particulate matter)		
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
Occupational exposure lim	its of decompo	sition products		
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REI
		ST	250 ppm 325 mg/m3	NIOSH REI
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		TWA	200 ppm 260 mg/m3	OSHA P0
		STEL	250 ppm 325 mg/m3	OSHA P0
Engineering measures	Local exha It is recom local exhau involved in vents or ar	ust ventilation and handling of this p		systems osion relief
Personal protective equipr	nent			
Respiratory protection	In the case	dust developmen	t use dust mask. tion use a respirator	
	limit they n The filter c maximum (gas/vapou handling th	filter. kers are facing conust use appropri- lass for the respirexpected contamur/aerosol/particul ne product. If this	ncentrations above ate certified respirate ator must be suitable inant concentration ates) that may arise concentration is exc	the exposure ors. e for the when
Hand protection	When worl limit they n The filter c maximum (gas/vapou handling th	filter. kers are facing conust use appropri- lass for the respirexpected contamur/aerosol/particul ne product. If this	ncentrations above ate certified respirate ator must be suitabl inant concentration ates) that may arise	the exposure ors. e for the when
Material	When worl limit they n The filter c maximum (gas/vapou handling th contained : butyl-rubbe	filter. kers are facing con nust use appropri- lass for the respir expected contam ur/aerosol/particul he product. If this breathing apparate	ncentrations above ate certified respirate ator must be suitable inant concentration ates) that may arise concentration is exc	the exposure ors. e for the when
•	When worl limit they n The filter c maximum (gas/vapou handling th contained	filter. kers are facing con nust use appropri- lass for the respir expected contam ur/aerosol/particul he product. If this breathing apparate	ncentrations above ate certified respirate ator must be suitable inant concentration ates) that may arise concentration is exc	the exposure ors. e for the when
Material Break through time	When worl limit they n The filter c maximum (gas/vapou handling th contained : butyl-rubbe : >= 480 min	filter. kers are facing conust use appropria lass for the respir expected contam ur/aerosol/particul he product. If this breathing apparate er h	ncentrations above ate certified respirate ator must be suitable inant concentration ates) that may arise concentration is exc	the exposure ors. e for the when



sion 6.0	Revision Date 04/25/2024	Former date 10/26/2
Remarks	: Please observe the instructions r breakthrough time which are pro- gloves. Also take into considerati conditions under which the produ	vided by the supplier of the on the specific local
Eye protection Skin and body protection Hygiene measures	 danger of cuts, abrasion, and the Safety glasses Protective clothing When using do not eat, drink or s Wash hands before breaks and a 	moke.
TION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: pellets	
Colour	: natural colour	
Odour	: odourless	
Odour Threshold	: Methanol: Do NOT rely on the o the exposure limit.	dour: olfactory level is above
рН	: Not applicable insoluble	
Melting range	: 212 - 284 °F / 100 - 140 °C	
Boiling range	: Decomposes on heating.	
Flash point	: Not applicable (solid)	
Evaporation rate	: Not applicable (solid)	
Flammability (solid, gas)	: The product is not flammable.	
Upper explosion limit / Upper flammability limit	: Not applicable	
Lower explosion limit / Lower flammability limit	: Not applicable	
Vapour pressure	: Not applicable (solid)	
Relative vapour density	: Not applicable	
Density	: 0.9 - 1.0 g/cm ³	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: Not applicable insoluble	



Visico LE4439

Version 6.0		Revision Date 04/25/2024	Former date 10/26/2023
Auto-ignition temperature	:	> 608 °F / > 320 °C	
Viscosity Viscosity, kinematic	:	No data available	
Explosive properties	:	Not explosive	
Oxidizing properties	:	The substance or mixture is not classified	d as oxidizing.
Particle size	:	3 - 10 mm Method: Image analysis (surface-based)	

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability	:	Stable under recommended storage conditions. The product is a stable thermoplastic, with no chemical reactivity. The intended crosslinking reaction occurs in combination with the base resin and moisture: at ambient conditions, in sauna or hot water bath.
Possibility of hazardous reactions	:	In contact with water or moisture methanol will be released.
Conditions to avoid	:	Exposure to moisture Extremes of temperature and direct sunlight.
Incompatible materials Hazardous decomposition products		None known. Under fire conditions: Carbon monoxide During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released. During crosslinking reaction in combination with base resin: methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.



Visico LE4439

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

- **IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage the unborn child.

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Causes damage to organs (Immune system) through prolonged or repeated exposure.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released. Methanol: Toxic by inhalation, in contact with skin and if swallowed. Causes damage to organs.

 Remarks
 : Inhalation of dust may irritate the respiratory tract.

 Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

Product:



Visico LE4439

Version 6.0		Revision Date 04/25/2024	Former date 10/26/2023
Biodegradability	:	Remarks: Not readily biodegradable.	
Bioaccumulative potential			
<u>Product:</u> Bioaccumulation	:	Remarks: Does not accumulate in orga	anisms.
Mobility in soil			
Product: Mobility	:	Remarks: Not expected to adsorb on s Remarks: The product is insoluble and	
Other adverse effects			
Product: Additional ecological information	:	Should not be released into the enviro	nment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: This substance, when discarded or disposed of is not specifically listed as a hazardous waste in Federal regulations. However, it could be hazardous if it is considered toxic, corrosive, ignitable or reactive according to Federal definitions (40 CFR 261). Additionally, it could be designated as hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact or mixing may have occurred, check 40 CFR 261 to determine whether it is a hazardous waste.
	The transportation, storage, treatment and disposal of this waste material must be conducted in accord-ance with all applicable Federal, state and local regulations.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good



sion 6.0	Revision Date 04/25/2024	Former date 10/26/2
IMDG-Code Not regulated as a dangerou	s good	
Transport in bulk according	g to Annex II of MARPOL 73/78 an	d the IBC Code
Not applicable for product as	supplied.	
National Regulations		
49 CFR Not regulated as a dangerou	s good	
Special precautions for use	er	
Remarks	: Not dangerous goods in the m IMDG-Code, ICAO/IATA-DGR	eaning of ADR/RID, ADN,
TION 15. REGULATORY INI	FORMATION	
US State Regulations		
Massachusetts Right To Ki	now	
zinc dioctadecano		557-05-1
Pennsylvania Right To Kno	ow	
poly[ethene-co-(et zinc dioctadecano	hyl 2-propenoate)]	9010-86-0 557-05-1
Maine Chemicals of High C	oncern	
Product does not o	contain any listed chemicals	
Vermont Chemicals of High	n Concern	
Product does not o	contain any listed chemicals	
Washington Chemicals of I	High Concern	
Product does not o	contain any listed chemicals	
California Prop. 65		
This product does not contain defects, or any other reprodu	n any chemicals known to State of C ictive harm.	alifornia to cause cancer, birth
California List of Hazardou	s Substances	
		3648-18-8 557-05-1
California Permissible Exp	osure Limits for Chemical Contam	inants
dioctyltin dilaurate3648-18-8zinc dioctadecanoate557-05-1		
Safety, health and environr	nental regulations/legislation spe	cific for the substance or

orders under TSCA and that Borealis is not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.



Visico LE4439

Version 6.0	Revision Date 04/25/2024	Former date 10/26/2023
Manufacturing, Processing, and	r the Prevention of Fire and Dust Exp Handling of Combustible Particulate elled in accordance with Hazard Con	Solids, for safe handling.


(29 CFR 1910.1200) US. Drug Enforcement Administration (DEA) Listed Precursor and Essential Chemicals (21 CFR 1310)

: Not applicable

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Table Z-1-A Limits for Air Contaminants (1989 vacated
OSHA Z-1	:	values) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA		8-hour, time-weighted average
ACGIH / STEL		Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA		8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit

Borealis AG | Trabrennstrasse 6-8 | 1020 Vienna | Austria Telephone +43 1 224 00 0 | Fax +43 1 22 400 333

FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



Visico LE4439

Version 6.0

Revision Date 04/25/2024

Former date 10/26/2023

OSHA Z-1 / TWA

: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Sources of key data used to compile the Safety Data	:	Safety data sheets of raw material suppliers.
Sheet		
Revision Date	:	04/25/2024



Visico LE4439

Version 6.0

Revision Date 04/25/2024

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

US / EN

