

Polypropylene

Purpolen™ PPY40

Post-Consumer Recyclate



Description

Purpolen™ PPY40 is a grey polypropylene post-consumer recyclate supplied in pellets. This product is an ideal PP, used where sustainability and circularity matter. It is a post-consumer recyclate including a large part of recycled post-consumer waste coming from pre-sorted municipality waste. It is a part of EuCertPlast certificate according to European Standard EN15343:2007 (certificate available upon request).

It is not intended for use in beverages, drinking water contact, food contact, medical, pharmaceutical or healthcare applications. Due to the nature of recyclates, some variation in colour can be observed between batches.

Homogenised 24 tonne- truckloads

Pellet shape: cylindrical

Pore size of filter: 180 µm

Applications

Injection moulding applications

Special Features

Good stiffness / impact balance and low odour

Good demoulding properties

Physical Properties

Property	Typical Value	Test Method
Data should not be used for specification work		
Density	915 kg/m ³	ISO 1183
Melt Flow Rate (230 °C/2,16 kg)	40 g/10min	ISO 1133
Tensile Modulus (1 mm/min)	1.200 MPa	ISO 527-2
Tensile Stress at Yield (50 mm/min)	24 MPa	ISO 527-2
Charpy Impact Strength, notched (23 °C)	5,5 kJ/m ²	ISO 179/1eA
Moisture content (105 °C)	< 0,1 %	Moisture analyser (infrared)
Ash content (650 °C) ¹	<= 1 %	ISO 1172

¹ Refers to filler content

Processing Techniques

This product is easy to process with standard injection moulding machines.

Following parameters should be used as guidelines:

Melt temperature	210 - 260 °C	Minimum to avoid sink marks.
Holding pressure	200 - 500 bar	
Mould temperature	30 - 40 °C	
Injection speed	High	

Shrinkage 1 - 2 %, depending on wall thickness and moulding parameters

Purpolen is a trademark of the Borealis group.

mtm plastics GmbH | Bahnhofstraße 106 | D-99759 Niedergebra | Germany
Tel. +49 (0) 36338 / 325-0 | Fax +49 (0) 36338 / 325-25
info@mtm-plastics.eu | www.mtm-plastics.eu



Polypropylene

Purpolen PPY40

Storage

Purpolen PPY40 should be stored in dry conditions at temperatures below 50°C and protected from UV-light. Improper storage can initiate degradation, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.

Safety

Please see our "Safety data sheet" / "Product safety information sheet" for details on various aspects of safety, recovery and disposal of the product. For more information, contact your Borealis representative.

Related Documents

The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.

"Safety data sheet" / "Product safety information sheet"
Recovery and disposal of polyolefins
Information on emissions from processing and fires

Disclaimer

Recycled plastics are subject to material inconsistencies. mtm makes no warranties which extend beyond the description contained herein and to the best of our knowledge, the information is accurate and reliable as of the date of publication. Because of the multitude of possible influences during the use and application of our products, the information included does not release customers and users from the obligation to examine and test them carefully. Please note that nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose. It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose as mtm do not know the origin of the product. Where necessary, the customer is recommended to obtain a feedstock release from the customer. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products. No liability can be accepted in respect of the use of any mtm product in conjunction with any other products and/or materials. The information contained herein relates exclusively to our products when not used in conjunction with any other material unless as specifically provided for in the test methods stated above. The product(s) mentioned herein are not intended to be used for food contact, drinking water contact, medical, pharmaceutical or healthcare applications and we do not support their use for such applications. Otherwise, our General Terms and Conditions of Sale apply.