

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat™ LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Ambicat LE4476

Unique Formula Identifier (UFI) : DTW1-UT2J-TD3M-6UXW

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Raw material for plastics industry

#### 1.3 Details of the supplier of the safety data sheet

Supplier : Borealis AG  
Trabrennstrasse 6-8, 1020 Vienna, Austria  
Telephone: +43 1 22400 0

E-mail address : [sds@borealisgroup.com](mailto:sds@borealisgroup.com)

#### 1.4 Emergency telephone number

+1 760 476 3962 (3E), Access code: 336296

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Reproductive toxicity, Category 2 H361d: Suspected of damaging the unborn child.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Warning

Hazard statements : H361d Suspected of damaging the unborn child.

Precautionary statements : **Prevention:**

Ambicat is a trademark of the Borealis group.

Borealis AG | Trabrennstrasse 6-8 | 1020 Vienna | Austria  
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333  
FN 269858a | CCC Commercial Court of Vienna | Website [www.borealisgroup.com](http://www.borealisgroup.com)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The product burns, but is not classified as flammable.

Dust from the product gives a potential risk for dust explosion.

During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released.

In contact with water or moisture methanol will be released.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : The product is a silane crosslinkable polyethylene copolymer.

### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

	Index-No. Registration number		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	68610-51-5 271-867-2 01-2119496062-39	Repr. 2; H361d Aquatic Chronic 4; H413	>= 3 - < 10
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	85536-14-7 287-494-3 01-2119490234-40	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Seek medical advice immediately.
- In case of skin contact : If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage.  
Obtain medical attention.  
  
Wash off with soap and plenty of water.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse thoroughly with plenty of water, also under the eyelids.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, rinse mouth with water (only if the person is conscious).  
Seek medical advice immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation of dust may irritate the respiratory tract.  
Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.
- Symptoms of poisoning (methanol):  
Daze  
Dizziness  
Nausea

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

Abdominal pain  
Respiratory disorders

Symptoms of poisoning, prolonged exposure (methanol):  
Blindness

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water in spread jet, dry chemicals, foam or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Principal toxicant in the smoke is carbon monoxide.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.  
Use personal protective equipment.

### 6.2 Environmental precautions

Should not be released into the environment.

It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment.

### 6.3 Methods and material for containment and cleaning up

Vacuum or sweep up spill.  
All spill of material must be removed immediately to prevent slipping accidents.  
Recycle or dispose loose material properly.  
Do not flush into surface water or sanitary sewer system.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### 6.4 Reference to other sections

For personal protection see section 8.  
For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released. Provide adequate ventilation. Local exhaust ventilation may be necessary. Avoid inhalation of dust and decomposition fumes. Avoid contact with skin and eyes.

Advice on protection against fire and explosion : Dust from the product gives a potential risk for dust explosion. All equipment shall be grounded. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up.

Further information on storage stability : Keep in a dry place.

### 7.3 Specific end use(s)

Specific use(s) : Raw material for wire and cable applications.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

For national exposure limit (OEL) values, check country specific safety data sheets.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methanol	67-56-1	TWA	200 ppm 260 mg/m <sup>3</sup>	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	Workers	Oral	Long-term exposure	0,8 mg/kg
Remarks:	Exposure time: 24 hrs			
	Workers	Dermal	Long-term exposure	4 mg/kg
Remarks:	Exposure time: 24 hrs			
	Workers	Inhalation	Long-term exposure	0,35 mg/m3
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	Workers	Skin contact	Long-term systemic effects	170 mg/kg bw/d
	Workers	Inhalation	Long-term systemic effects, Long-term local effects	12 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	Sewage treatment plant	150,9 mg/l

## 8.2 Exposure controls

### Engineering measures

Provide adequate ventilation.  
Local exhaust ventilation may be necessary.

### Personal protective equipment

Eye protection : Safety glasses  
Use eye protection according to EN 166.

Hand protection  
Material : Nitrile rubber

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
Protective gloves complying with EN 374.

Skin and body protection : Protective clothing

Respiratory protection : In case of insufficient ventilation: Respirator with ABEK-P3 filter or self-contained breathing apparatus.  
In case of dust development use dust mask.

Protective measures : Appropriate personal protective equipment (PPE) shall be worn in accordance with Regulation (EU) 2016/425.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### Environmental exposure controls

General advice : Should not be released into the environment.  
It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of plastics in to the environment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: pellets
Colour	: beige
Odour	: acrylic-like
Odour Threshold	: Methanol: Do NOT rely on the odour: olfactory level is above the exposure limit.  >= 0,00096 ppm Butyl acrylate
Melting point/range	: 100 - 140 °C
Boiling range	: Decomposes on heating.
Flammability	: The product is not flammable.
Upper explosion limit / Upper flammability limit	: Not applicable
Lower explosion limit / Lower flammability limit	: Not applicable
Flash point	: Not applicable, (solid)
Auto-ignition temperature	: > 320 °C
pH	: Not applicable insoluble
Viscosity	
Viscosity, kinematic	: No data available
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable (solid)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

Vapour pressure	:	Not applicable (solid)
Density	:	0,9 - 1,0 g/cm <sup>3</sup>
Particle size	:	3 - 10 mm Method: Image analysis (surface-based)

### 9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Evaporation rate	:	Not applicable (solid)

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.

### 10.2 Chemical stability

The product is a stable thermoplastic.

The intended crosslinking reaction occurs in combination with the base resin and moisture: at ambient conditions, in sauna or hot water bath.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : In contact with water or moisture methanol will be released.

### 10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Under fire conditions:

Carbon monoxide

During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released.

During crosslinking reaction in combination with base resin: methanol

In contact with water or moisture methanol will be released.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### Components:

##### **Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.:**

Acute oral toxicity : LD50 (Rat): 1.470 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Read-across (Analogy)

##### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

##### Product:

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439  
Result : No skin irritation

##### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

##### Product:

Species : Bovine cornea  
Method : OECD Test Guideline 437  
Result : No eye irritation

##### Respiratory or skin sensitisation

##### Skin sensitisation

Based on available data, the classification criteria are not met.

##### Respiratory sensitisation

Based on available data, the classification criteria are not met.

##### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

##### Carcinogenicity

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### Reproductive toxicity

Suspected of damaging the unborn child.

#### Components:

#### Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Effects on fertility : Test Type: Pre-/postnatal development  
Species: Rabbit, female  
Application Route: Oral  
Dose: 50 mg/kg  
Method: OECD Test Guideline 414  
Result: Some evidence of adverse effects on development, based on animal experiments.  
GLP: yes

### STOT - single exposure

Based on available data, the classification criteria are not met.

### STOT - repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : During crosslinking reaction in combination with base resin: methanol (Flam. Liq. 2; H225, Acute Tox. 3; H301, Acute Tox. 3; H311, Acute Tox. 3; H331, STOT SE 1; H370) is released. Methanol: Toxic by inhalation, in contact with skin and if swallowed. Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

Remarks : Information given is based on tests on the mixture itself. Information given is based on data of the components.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: No effect up to the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No effect up to the limit of solubility.
- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (fresh water algae)): > 0,2 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: No effect up to the limit of solubility.

### 12.2 Persistence and degradability

#### Product:

- Biodegradability : Remarks: Not readily biodegradable.

### 12.3 Bioaccumulative potential

#### Product:

- Bioaccumulation : Remarks: Does not accumulate in organisms.

### 12.4 Mobility in soil

#### Product:

- Mobility : Remarks: Not expected to adsorb on soil.  
Remarks: The product is insoluble and floats on water.

### 12.5 Results of PBT and vPvB assessment

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Should not be released into the environment.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of contents/ container to an approved waste disposal plant.  
Check with local regulations.

Contaminated packaging : Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not dangerous goods in the meaning of ADR/RID, ADN, IMDG-Code, ICAO/IATA-DGR

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

### 15.2 Chemical safety assessment

no

---

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H361d : Suspected of damaging the unborn child.  
H412 : Harmful to aquatic life with long lasting effects.  
H413 : May cause long lasting harmful effects to aquatic life.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
2006/15/EC : Europe. Indicative occupational exposure limit values  
2006/15/EC / TWA : Limit Value - eight hours

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Ambicat LE4476

Version 19.0

Revision Date: 24.04.2024

Former date: 24.04.2024

### Further information

- Other information : Issued according to Regulation (EC) No 1907/2006, Annex II, and its amendments.  
Changes since the last version are highlighted in the margin.  
This version replaces all previous versions.
- Issuer : Borealis, Group Product Stewardship
- Sources of key data used to compile the Safety Data Sheet : The classification information of components is based on raw material supplier data.  
  
Information given is based on tests on the mixture itself.  
Information given is based on data of the components.

### Classification of the mixture:

Repr. 2                      H361d

### Classification procedure:

Calculation method

### Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

**Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.**

**It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.**

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.