Borlink™ LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : Borlink LE4201EHV

Manufacturer or supplier's details

Company : Borealis AG

Address : Wagramer Strasse 17-19, 1220 Vienna, Austria

Telephone : +43 1 22400 0

Emergency telephone number : +44 (0) 1235 239 670 (NCEC Carechem 24)

E-mail address : sds@borealisgroup.com

Recommended use of the chemical and restrictions on use

Recommended use : raw material for plastics industry

Restrictions on use : Use only according to our recommendations.

2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 3

Skin sensitisation : Category 1

GHS-Labelling

Hazard pictograms

Signal word : Warning

Hazard statements : H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P261 Avoid breathing dust.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

Borlink is a trademark of the Borealis group.



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Other hazards which do not result in classification

The product burns, but is not classified as flammable. Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : The product is a polyethylene polymer.

Hazardous components

Chemical name	CAS-No.	Classification	MAC value mg/m3 / TSEL value	Concentration (% w/w)
polyethene	9002-88-4		MPC-STEL: 10 mg/m3 Class 4 - Low hazard	> 90
bis(α,α-dimethylbenzyl) peroxide	80-43-3	Org. Perox. C; H242 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Aquatic Chronic 2; H411		>= 1 - < 2,5
6,6'-di-tert-butyl-4,4'-thiodi-m-cresol	96-69-5	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		>= 0,1 - < 0,25

For explanation of abbreviations see section 16.



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of vapours or

decomposition products.

In case of skin contact : Wash off with soap and plenty of water.

Call a physician if irritation develops or persists.

If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as

removal could result in severe tissue damage.

Obtain medical attention.

In case of eye contact : Flush eyes with water as a precaution.

If swallowed : Rinse mouth with water.

Most important symptoms and effects, both acute and

delayed

: Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products

may give headache or irritation of the respiratory tract.

Prolonged skin contact may give skin irritation caused by the peroxide content present on the surface of the granules.

May cause an allergic skin reaction.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Flammable properties

Flash point

Not applicable (solid)

Ignition temperature : > 320 °C

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Flammability (solid, gas) : The product is not flammable.

Suitable extinguishing media : Water in spread jet, dry chemicals, foam or carbon dioxide.



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

Specific hazards during

firefighting

: Principal toxicant in the smoke is carbon monoxide.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering environment and drains.

Methods and materials for containment and cleaning up

: Vacuum or sweep up spill.

All spill of material must be removed immediately to prevent

slipping accidents.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Dust from the product represents a risk for dust explosions when dispersed with air in a sufficient concentration and with the presence of an ignition source. All equipment shall be grounded. Routine housekeeping will also contribute in

preventing risks of dust explosions.

Advice on safe handling : During processing and thermal treatment of the product, small

amounts of volatile hydrocarbons may be released. Avoid inhalation of dust and decomposition fumes.

Avoid contact with skin and eyes.

The product contains small amounts of a substance classified as sensitising, which may produce an allergic reaction to

susceptible personnel.

Personnel sensitised to this substance should not be allowed

to handle the product.

Conditions for safe storage

: Safety aspects do not require any special precautions in terms

of storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Data Source
		(Form of	parameters /	
		exposure)	Permissible	



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

			concentration	
polyethene	9002-88-4	MPC-STEL (aerosol)	10 mg/m3	RU OEL
	Further inforn	nation: Class 4 -	Low hazard	

Engineering measures : Provide adequate ventilation.

Local exhaust ventilation may be necessary.

Personal protective equipment

Respiratory protection : Ensure adequate ventilation.

In case of dust development use dust mask.

Hand protection

Remarks : Wear suitable gloves: neoprene , Nitrile rubber or butyl-

rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday. Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pellets

Colour : natural colour

Odour : odourless

pH : Not applicable insoluble

Melting range : 100 - 140 °C

Boiling range : Decomposes on heating.

Flash point : Not applicable (solid)

Evaporation rate : Not applicable (solid)



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : Not applicable (solid)

Density : 0,9 - 1,0 g/cm³

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Not applicable insoluble

Auto-ignition temperature : > 320 °C

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : The product is a stable thermoplastic with no chemical

reactivity below 140°C. Above 140°C the intended

crosslinking reaction occurs.

Possibility of hazardous

reactions

None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Reducing agents

Strong acids and strong bases

Hazardous decomposition

products

Under fire conditions: Carbon monoxide

During processing and thermal treatment of the product, small



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

amounts of volatile hydrocarbons may be released.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes mild skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

Toxicity to daphnia and other

aquatic invertebrates

: NOEC (Daphnia magna (Water flea)):

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Remarks: No effect up to the limit of solubility.

Read-across (Analogy)

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)):

End point: Growth rate
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

GLP: yes

Remarks: No effect up to the limit of solubility.

Read-across (Analogy)

Components:

6,6'-di-tert-butyl-4,4'-thiodi-m-cresol:

Toxicity to fish : LC50 (fathead minnow (Pimephales promelas)): 0,36 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0,16 mg/l

Exposure time: 48 h

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not accumulate in organisms.

Components:

bis(α , α -dimethylbenzyl) peroxide:

Bioaccumulation : Bioconcentration factor (BCF): 137 - 1.470

Exposure time: 56 d Temperature: 25 °C Concentration: 0,01 mg/l

Mobility in soil

Product:

Mobility : Remarks: The product is insoluble and floats on water.

Not expected to adsorb on soil.



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

Other adverse effects

Product:

Additional ecological

information

: The product is not classified as hazardous for the

environment.

Information given is based on tests on mixtures with similar

compositions.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Reuse or recycle if not contaminated.

The product may be safely used as fuel.

Proper combustion does not require any special flue gas

control.

Check with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. TRANSPORT INFORMATION

ADR

Not regulated as a dangerous good

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: -02.01.2020 Date of first issue: 02.01.2020

Toxic to aquatic life with long lasting effects.

16. OTHER INFORMATION

H411

Full text of H-Statements

H242	Heating may cause a fire.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation : Organic peroxides Org. Perox. Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory: TSCA -Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations



Borlink LE4201EHV

Version 4.0 Revision Date: Date of last issue: - 02.01.2020 Date of first issue: 02.01.2020

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : SDS According to GOST 30333-2007

Issuer : Borealis, Group Product Stewardship / Aino Haritonova

Sources of key data used to compile the Safety Data

Sheet

: Information given is based on tests on mixtures with similar compositions., The classification information of components is

based on raw material supplier data.

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

