

SAFETY DATA SHEET

Daplen™ EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : Daplen EH227AE-9550

Manufacturer or supplier's details

Supplier : Borealis AG

Address : Wagramer Strasse 17-19, 1220 Vienna, Austria

Telephone : +43 1 22400 0

Emergency telephone number : +44 (0) 1235 239 670 (NCEC Carechem 24)

E-mail address : sds@borealisgroup.com

Recommended use of the chemical and restrictions on use

Recommended use : raw material for plastics industry

Restrictions on use : Use only according to our recommendations.

2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitisation : Category 1

GHS-Labeling

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Daplen is a trademark of the Borealis group.

Borealis AG | Wagramer Strasse 17-19 | 1220 Vienna | Austria
Telephone +43 1 224 00 0 | Fax +43 1 22 400 333
FN 269858a | CCC Commercial Court of Vienna | Website www.borealisgroup.com



SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

P362 + P364 Take off contaminated clothing and wash it before reuse.

Other hazards which do not result in classification

The product burns, but is not classified as flammable. Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : The product is an elastomer modified polypropylene.
It contains talc.
It contains colorants.

Hazardous components

Chemical name	CAS-No.	Classification	MAC value mg/m ³ / TSEL value	Concentration (% w/w)
magnesium silicate	14807-96-6			20 - 30
N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethyl piperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine	106990-43-6	Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Chronic 2; H411		>= 0,25 - < 1
bis(2,2,6,6-tetramethyl-4-piperidinyloxy)decane-1,10-diol	52829-07-9	Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 2; H411		>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of vapours or decomposition products.

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

In case of skin contact	: Wash off with soap and plenty of water. Get medical attention if irritation develops and persists. If molten material comes in contact with the skin, cool with plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage. Obtain medical attention.
In case of eye contact	: Rinse with water.
If swallowed	: Rinse mouth with water.
Most important symptoms and effects, both acute and delayed	: Inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract. May cause an allergic skin reaction.
Notes to physician	: Treat symptomatically.

5. FIREFIGHTING MEASURES

Flammable properties

Flash point	: Not applicable (solid)
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Flammability (solid, gas)	: The product is not flammable.
Suitable extinguishing media	: Water in spread jet, dry chemicals, foam or carbon dioxide.
Specific hazards during firefighting	: Principal toxicant in the smoke is carbon monoxide.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Use personal protective equipment.
---	--

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

- Environmental precautions : Prevent product from entering environment and drains.
- Methods and materials for containment and cleaning up : Vacuum or sweep up spill.
All spill of material must be removed immediately to prevent slipping accidents.

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Dust from the product represents a risk for dust explosions when dispersed with air in a sufficient concentration and with the presence of an ignition source. All equipment shall be grounded. Routine housekeeping will also contribute in preventing risks of dust explosions.
- Advice on safe handling : During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released. Avoid inhalation of dust and decomposition fumes. Avoid contact with skin and eyes. Wear suitable gloves. The product contains small amounts of a substance classified as sensitising, which may produce an allergic reaction to susceptible personnel. Personnel sensitised to this substance should not be allowed to handle the product.
- Conditions for safe storage : Safety aspects do not require any special precautions in terms of storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
magnesium silicate	14807-96-6	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				

However, as the chemical is embedded in a solid polymer, exposure is unlikely, unless the polymer is processed in a way that makes such exposure possible.

- Engineering measures** : Provide adequate ventilation.
Local exhaust ventilation may be necessary.

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

Personal protective equipment

Hand protection

Material : Nitrile rubber

Remarks

: Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection

: Safety glasses

Skin and body protection

: Protective suit

Hygiene measures

: When using do not eat, drink or smoke.
Wash hands before breaks and at the end of workday.
Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: pellets

Colour

: black

Odour

: odourless

pH

: No data available

Melting range

: 130 - 170 °C

Boiling range

: Decomposes on heating.

Flash point

: Not applicable (solid)

Evaporation rate

: Not applicable (solid)

Flammability (solid, gas)

: The product is not flammable.

Upper explosion limit

: Not applicable

Lower explosion limit

: Not applicable

Vapour pressure

: Not applicable (solid)

Density

: 1,1 - 1,2 g/cm³

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

Bulk density	: No data available
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable insoluble
Viscosity Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

10. STABILITY AND REACTIVITY

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: The product is a stable thermoplastic.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: Under fire conditions: Carbon monoxide

During processing and thermal treatment of the product, small amounts of volatile hydrocarbons may be released.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

bis(2,2,6,6-tetramethyl-4-piperidinyl)decanedioate:

Acute oral toxicity : LD50 (Rat): 3.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,5 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

Acute dermal toxicity : LD50 (Rat): > 3.170 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bis(2,2,6,6-tetramethyl-4-piperidinyl)decanedioate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,57 mg/l
Exposure time: 48 h
Test Type: Short term

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

M-Factor (Acute aquatic toxicity) : 1
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): 0,96 mg/l
Exposure time: 21 d

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not accumulate in organisms.

Mobility in soil

Product:

Mobility : Remarks: The product is insoluble and sinks in water.
Not expected to adsorb on soil.

Other adverse effects

Product:

Additional ecological information : The product is not classified as hazardous for the environment.

Hygienic standards:

(Allowable concentration in air, water, including fishery waters, soil)

Components	Air	Water	Soil	Data Source
magnesium silicate 14807-96-6	TSEL value: 0,5 mg/m3	TSEL value: 0,25 mg/l Limiting health hazard indicator: organoleptic; increases the turbidity of the water Hazard class: Class 4 - low hazard		List 2 List 3

List 2: GN 2.1.6.2309-07 Tentative safe exposure level (TSEL) of pollutants in the air of settlements

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

List 3: GN 2.1.5.2307-07 Tentative safe exposure level (TSEL) of Chemical Substances Contained in Water of Water Bodies for Economic-Potable and Social-Domestic Water Use

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Reuse or recycle if not contaminated.
The product may be safely used as fuel.
Proper combustion does not require any special flue gas control.
Check with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

ADR

Not regulated as a dangerous good

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

16. OTHER INFORMATION

Full text of H-Statements

- H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H373 May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : SDS According to GOST 30333-2007
Issuer : Borealis, Group Product Stewardship / Aino Haritonova
Sources of key data used to compile the Safety Data Sheet : The classification information of components is based on raw material supplier data.

SAFETY DATA SHEET

Daplen EH227AE-9550

Version 5.0

Revision Date:
02.01.2020

Date of last issue: -
Date of first issue: 02.01.2020

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.