Daplen™ EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

SECTION 1. IDENTIFICATION

Product name : Daplen EH227AEU-9550

Manufacturer or supplier's details

Supplier : Borealis Compounds Inc

176 Thomas Road, NJ 07865 Port Murray, United States of

America (USA)

Telephone: +1 908 850 6200

E-mail address : sds@borealisgroup.com

Emergency telephone +1 866 519 4752 (3E) Access code: 336296Borealis

number Compounds Inc, Borealis North America HSE: 908-850-6200

for Monday - Friday 8-4:30pm excluding holidays

Recommended use of the chemical and restrictions on use

Recommended use : Raw material for plastics industry

Restrictions on use : Use only according to our recommendations.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Daplen is a trademark of the Borealis group.



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

Warning!

May form combustible dust concentrations in air (during processing).

The product burns, but is not classified as flammable.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Chemical nature The product is a polypropylene copolymer.

It contains talc.

It contains carbon black.

Components

Chemical name	CAS-No.	Concentration (% w/w)
magnesium silicate	14807-96-6	>= 20 - < 30
carbon black	1333-86-4	>= 1 - < 5
magnesium carbonate	546-93-0	>= 1 - < 5
N,N,N,N-tetrakis(4,6-bis(butyl-(N-	106990-43-6	>= 0.1 - < 1
methyl-2,2,6,6-tetramethyl piperidin-		
4-yl)amino)triazin-2-yl)-4,7-		
diazadecane-1,10-diamine		
bis(2,2,6,6-tetramethyl-4-	52829-07-9	>= 0.1 - < 1
piperidinyl)decanedioate		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled Move to fresh air.

> If symptoms persist, call a physician. Wash off with soap and plenty of water.

In case of skin contact Call a physician if irritation develops or persists.

If molten material comes in contact with the skin, cool with

plenty of water. DO NOT remove solidified product, as removal could result in severe tissue damage.

Flush eyes with water as a precaution.

In case of eye contact



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Get medical attention if irritation develops and persists.

If swallowed : Rinse mouth with water.

Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

: Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

Skin contact may provoke the following symptoms:

Irritation

May cause an allergic skin reaction. Suspected of damaging fertility.

Notes to physician : Treat symptomatically.

No specific instructions needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards during

firefighting

Water in spread jet, dry chemicals, foam or carbon dioxide.

High volume water jet

Principal toxicant in the smoke is carbon monoxide.

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment.

Environmental precautions : Should not be released into the environment.

It is recommended to implement systems and practices (such as Operation Clean Sweep®) to prevent accidental release of

plastics in to the environment.

Methods and materials for containment and cleaning up

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Non-sparking tools should be used.

Vacuum or sweep up spill.

All spill of material must be removed immediately to prevent

slipping accidents.

Recycle or dispose loose material properly.

Do not flush into surface water or sanitary sewer system.

SECTION 7. HANDLING AND STORAGE



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Advice on protection against :

fire and explosion

Dust from the product gives a potential risk for dust explosion.

All equipment shall be grounded.

Routine housekeeping should be instituted to ensure that

dusts do not accumulate on surfaces.

Advice on safe handling : During processing and thermal treatment of the product, small

amounts of volatile hydrocarbons may be released.

Provide adequate ventilation.

Local exhaust ventilation may be necessary. Avoid inhalation of dust and decomposition fumes.

Avoid contact with skin and eyes.

Conditions for safe storage : Safety aspects do not require any special precautions in terms

of storage.

Further information on

storage stability

Keep in a dry place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
magnesium silicate	14807-96-6	TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA	0.1 fibres per cubic centimeter	ACGIH
carbon black	1333-86-4	TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
magnesium carbonate	546-93-0	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total	15 mg/m3	OSHA Z-1



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

dust)		
TWA (respirable fraction)	5 mg/m3	OSHA Z-1
TWA (Total dust)	15 mg/m3	OSHA P0
TWA (respirable dust fraction)	5 mg/m3	OSHA P0

Engineering measures : Provide adequate ventilation.

Local exhaust ventilation may be necessary.

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen

deficient environment.

Personal protective equipment

Respiratory protection : In case of dust development use dust mask.

In the case of vapour formation use a respirator with an

approved filter.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Material : Nitrile rubber

Remarks : Protective gloves

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Eye protection : Safety glasses
Skin and body protection : Protective clothing

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pellets

Colour : black

Odour : odourless

BOREALIS

Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

pH : Not applicable insoluble

Melting point/range : 266 - 338 °F / 130 - 170 °C

Boiling range : Decomposes on heating.

Flash point : Not applicable (solid)

Evaporation rate : Not applicable (solid)

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapour pressure : Not applicable (solid)

Density : 1.1 - 1.2 g/cm³

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : Not applicable insoluble

octanol/water

Auto-ignition temperature : > 608 °F / > 320 °C

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : 3 - 10 mm

Method: Image analysis (surface-based)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : The product is a stable thermoplastic.

Possibility of hazardous : None known.



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

reactions

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : None known.

Hazardous decomposition : Under fire conditions: products : Carbon monoxide

During processing and thermal treatment of the product, small

amounts of volatile hydrocarbons may be released.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Components:

bis(2,2,6,6-tetramethyl-4-piperidinyl)decanedioate:

Acute oral toxicity : LD50 (Rat): 3,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): > 3,170 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

IARC Group 1: Carcinogenic to humans

magnesium silicate 14807-96-6

Group 2B: Possibly carcinogenic to humans

carbon black 1333-86-4

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

magnesium silicate (Silica, Crystalline (Respirable Size))

14807-96-6

Reproductive toxicity

Suspected of damaging fertility.

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products

may give headache or irritation of the respiratory tract.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bis(2,2,6,6-tetramethyl-4-piperidinyl)decanedioate:

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.57 mg/l

Exposure time: 48 h Test Type: Short term

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC50 (Daphnia magna (Water flea)): 0.96 mg/l

Exposure time: 21 d

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not accumulate in organisms.



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Mobility in soil

Product:

Mobility : Remarks: Not expected to adsorb on soil.

Remarks: The product is insoluble and sinks in water.

Other adverse effects

Product:

Additional ecological

information

Should not be released into the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : This substance, when discarded or disposed of is not

specifically listed as a hazardous waste in Federal regulations.

However, it could be hazardous if it is considered toxic,

corrosive, ignitable or reactive according to Federal definitions

(40 CFR 261). Additionally, it could be designated as

hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact or mixing may have occurred, check 40 CFR 261 to determine whether it is a

hazardous waste.

The transportation, storage, treatment and disposal of this waste material must be conducted in accord-ance with all

applicable Federal, state and local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Not regulated as a dangerous good

Special precautions for user

Remarks : Not dangerous goods in the meaning of ADR/RID, ADN,

IMDG-Code, ICAO/IATA-DGR

SECTION 15. REGULATORY INFORMATION

US State Regulations

Massachusetts Right To Know

magnesium silicate	14807-96-6
carbon black	1333-86-4
magnesium carbonate	546-93-0

Pennsylvania Right To Know

magnesium silicate	14807-96-6
poly[ethene-co-(1-octene)]	26221-73-8
poly[(1-propene)-co-ethene]	9010-79-1
carbon black	1333-86-4
polyethene	9002-88-4
polypropene	9003-07-0
zinc dioctadecanoate	557-05-1

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including magnesium silicate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

magnesium silicate	14807-96-6
carbon black	1333-86-4

California Permissible Exposure Limits for Chemical Contaminants

magnesium silicate	14807-96-6
carbon black	1333-86-4

California Regulated Carcinogens

magnesium silicate 14807-96-6



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Safety, health and environmental regulations/legislation specific for the substance or mixture


Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Borealis certifies that all chemical substances in this shipment comply with all applicable rules or orders under TSCA and that Borealis is not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.

The product is classified and labelled in accordance with Hazard Communication Standard 2012 (29 CFR 1910.1200)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Sources of key data used to : Safety data sheets of raw material suppliers.

compile the Safety Data

Sheet

Revision Date : 04/23/2024



Daplen EH227AEU-9550

Version 5.0 Revision Date 04/23/2024 Former date 06/06/2022

Disclaimer

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication; however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

US / EN

